Category 5e XCELERATOR™ Jack

By Hubbell Premise Wiring
Catalog Number HXJ5EEI

Telephone/Data, Jack, XCELERATOR, Cat 5e.

Features

- Third Party Verified Category 5E Component Compliant
- Exclusive 1-Punch Termination Reduces Termination Time by 75%
- Mating Cycles Exceed Industry Standard by Four Times
- Bulk Packaging Reduces Excess Waste on the Job

Application

Up to 2.5GBASE-T, 802.3bt POE

General

Color	Electric Ivory
Construction Material - Main	Thermoplastic
Contact	IDC: Phosphor Bronze with 100 Micro-Inch Tin Over Plating
Contact Point Material	Beryllium Copper with Gold Over Plating
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	Modular Jack
Material - Housing	High-impact thermoplastic (UL 94V-0)
Material - Mounting Hardware	Keystone
Mounting Type	Snap-fit
Operating Cycles	2000 Plug
Performance	TIA Cat 5e Component
Series	Cat 5e UTP
Size	0.86 (22) x 0.67 (17) x 1.29 (33)
Style	RJ-45 Jack
Temperature Rating	Max Continuous- 75° C, Minimum- -40° C Without Impact
Type	Modular Jack
UPC	662620825052

Dimensions

Display Size	Standard Sized Product

Electrical Ratings

Connectivity	RJ45 Jack to IDC Punch Down
Contact Resistance	100 Ohm
Withstand Voltage	1,000 Vac @ 60 Hz

Certifications and Compliance

Industry Standard(s)

- ANSI/TIA/EIA-568 Category 5e component
- UL 1863 - Communications-Circuit Accessory
- IEC60512-99-002 POE Disconnection Endruance
- UL 2043 - Suitable for Air-Handling Spaces
- RoHS Compliant

Logistics

Carton Quantity	25
Number of Pieces in Package	1

Product Assets

Catalog Page - Premise Catalog Page B-5