HUBBELL **Premise Wiring**

Category 6 XCELERATOR™ Jack

By Hubbell Premise Wiring Catalog # HXJ6EI

Telephone/Data, Jack, XCELERATOR, Cat 6



Features

- Third Party Verified Category 6 Component Compliant
- Exclusive 1-Punch Termination Reduces Termination Time by 75%
- Mating Cycles Exceed Industry Standard by Four Times
- Bulk Packaging Reduces Excess Waste on the Job

Performance

TIA Cat 6 Component, Third Party Verified

General

Catalog Number HXJ6FI

Construction Material - Main

Contact

Contact Point Material

EU RoHS Indicator

Item Type

Material - Housing

Material - Mounting Hardware Operating Cycles

Series

Size

Specifications

Style

Temperature Rating

Thermoplastic

IDC: Phosphor Bronze with 100

Micro-Inch Tin Over Plating

Beryllium Copper with Gold

Over Plating

Yes

Modular Jack

High-impact thermoplastic (UL

94V-0)

Kevstone 2000 Plug

Cat 6 UTP

0.86 (22) x 0.67 (17) x 1.29 (33)

• Housing - High impact thermoplastic (UL 94 V-0)

• IDC Contact - Phosphor bronze with 100 micro-inch tin over nickel under plating

• Nose Contact - Beryllium copper with precious metal plating with nickel under-

plating

RJ-45 Jack

Max Continuous- 75° C,

Minimum - -40° C Without

Impact

Dimensions

UPC

Standard Sized Product Display Size

Electrical Ratings

Connectivity RJ45 Jack to IDC Punch Down

100 Ohm Contact Resistance

Withstand Voltage 1.000 Vac @ 60 Hz

Certifications And Compliance

Industry Standard(s)

ANSI/TIA/EIA-568 Category

6 component

662620825267

• UL 1863 - Communications-

Circuit Accessory

IEC60512-99-002 POE

Disconnection Endruance

• UL 2043 - Suitable for Air-

Handling Spaces

RoHS Compliant

Logistics

Carton Quantity 25 Number of Pieces in Package

Product Assets

Catalog Page - PREM A6 CatalogPage

Catalog Page - PREM B5 CatalogPage

Catalog Page - PREM B05 Catalog Page

Catalog Page - PREM A06 Catalog Page

Catalogs - Premise Wiring Catalog

Literature - HDPJ High Density Jack Panels

Specifications - HXJ6EI Specification Sheet French

Specifications - HXJ6EI Specification Sheet English