

USOC XCELERATOR™ Jack

By Hubbell Premise Wiring
Catalog # [HXJUBK](#)



XCELERATOR™ RJ25 USOC modular jacks support various telephony applications. The innovative angled QuickLace™ termination towers provide ample room for lacing, accelerating the termination.

Features

- RJ-25 USOC (RJ-25) Jack
- Quick-Lace Towers Accelerate Termination
- Mating Cycles Exceed Industry Standard by Four Times

Application

Telephone

Performance

USOC

General

Catalog Number	HXJUBK
Color	Black
Construction Material - Main Contact	Thermoplastic IDC: Phosphor Bronze with 100 Micro-Inch Tin Over Plating
Contact Point Material	Beryllium Copper with Gold Over Plating
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	Modular Jack
Material - Housing	High-impact thermoplastic (UL 94V-0)
Material - Mounting Hardware	Keystone
Mounting Type	Snap-fit
Operating Cycles	2000 Plug
Series	USOC
Size	0.86 (22) x 0.67 (17) x 1.29 (33)
Specifications	<ul style="list-style-type: none">• Housing - High impact thermoplastic (UL 94 V-0)• IDC Contact - Phosphor bronze with 100 micro-inch tin over nickel under plating• Nose Contact - Beryllium copper with precious metal

Style	plating with nickel under-plating RJ-45 Jack
Temperature Rating	Max Continuous- 75° C, Minimum- -40° C Without Impact
Type	Modular Jack
UPC	662620824697

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

Electrical Ratings

Connectivity	RJ45 Jack to IDC Punch Down
Contact Resistance	100 Ohm
Withstand Voltage	1,000 Vac @ 60 Hz

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none">• 6-Position USOC Compliant• CSA Certified• Mechanical TIA-568• RoHS Compliant• UL Listed 1864
----------------------	--

Logistics

Carton Quantity	25
Number of Pieces in Package	1

Product Assets

- [Catalog Page - PREM B5 CatalogPage](#)
- [Catalog Page - PREM B05 Catalog Page](#)
- [Catalogs - Premise Wiring Catalog](#)
- [Literature - HDPJ High Density Jack Panels](#)
- [Specifications - HXJUBK Specification Sheet English](#)
- [Specifications - HXJUBK Specification Sheet French](#)