



# Category 5e XCELERATOR™ Jack

By Hubbell Premise Wiring  
Catalog # [HXJ5EW](#)

XCELERATOR™ Category 5e modular jacks exceed all TIA component level parameters to provide 2.5GBASE-T application assurance. The innovative angled QuickLace™ termination towers provide ample room for lacing, accelerating the termination.

## Application

- Up to 2.5GBASE-T, 802.3bt POE

## General

Color	<ul style="list-style-type: none"><li>White</li></ul>
Construction Material - Main Contact	Thermoplastic IDC: Phosphor Bronze with 100 Micro-Inch Tin Over Plating
Contact Point Material	Beryllium Copper with Gold Over Plating
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	Modular Jack
Material - Housing	High-impact thermoplastic (UL 94V-0)
Material - Mounting Hardware	Keystone
Mounting Type	Snap-fit
Operating Cycles	2000 Plug
Performance	TIA Cat 5e Component
Series	Cat 5e UTP
Size	0.86 (22) x 0.67 (17) x 1.29 (33)
Style	RJ-45 Jack
Temperature Rating	Max Continuous- 75° C, Minimum- -40° C Without Impact
Type	<ul style="list-style-type: none"><li>Modular Jack</li><li>Modular Jack</li></ul>
UPC	662620825076



## Dimensions

Display Size	Standard Sized Product
--------------	------------------------

## Electrical Ratings

Connectivity	RJ45 Jack to IDC Punch Down
Contact Resistance	100 Ohm
Withstand Voltage	1,000 Vac @ 60 Hz

## Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none"><li>ANSI/TIA/EIA-568 Category 5e component</li><li>UL 1863 - Communications-Circuit Accessory</li><li>IEC60512-99-002 POE Disconnection Endurance</li><li>UL 2043 - Suitable for Air-Handling Spaces</li><li>RoHS Compliant</li></ul>
----------------------	---

Standards - RoHS Compliance Status	CM
------------------------------------	----

## Logistics

Carton Quantity	25
Number of Pieces in Package	1
Pallet Quantity	7800

## Product Assets



A proud member of the Hubbell Family.