

Category 6 XCELERATOR[™] Jack

By Hubbell Premise Wiring Catalog # HXJ6OR

Telephone/Data, Jack, XCELERATOR, Cat 6



• Up to 5GBASE-T, 802.3bt POE

General

Color	Orange
Construction Material - Main Contact	Thermoplastic IDC: Phosphor Bronze with 100 Micro-Inch Tin Over
Contact Point Material	Plating Beryllium Copper with Gold Over Plating
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	Modular Jack
Material - Housing	High-impact thermoplastic (UL 94V-0)
Material - Mounting Hardware	Keystone
Mounting Type	Snap-fit
Operating Cycles	2000 Plug
Performance	TIA Cat 6 Component, Third Party Verified
Series	Cat 6 UTP
Size	0.86 (22) x 0.67 (17) x 1.29 (33)
Style	RJ-45 Jack
Temperature Rating	Max Continuous- 75° C, Minimum40° C Without Impact
Туре	 Modular Jack
	Modular Jack
UPC	662620825366



Dimensions

Display Size

Electrical Ratings

Connectivity	RJ45 Jack to IDC Punch Down
Contact Resistance	100 Ohm
Withstand Voltage	1,000 Vac @ 60 Hz

Withstand Voltage 1,000 Vac @ 60 Hz
Certifications And Compliance

Industry Standard(s) • ANSI/TIA/EIA-568

	Category 6 component
•	UL 1863 - Communications- Circuit Accessory
•	IEC60512-99-002 POE Disconnection Endruance
•	UL 2043 - Suitable for Air- Handling Spaces

• RoHS Compliant

Standard Sized Product

Standards - RoHS Compliance CM Status

Logistics

Carton Quantity	25
Number of Pieces in Package	1
Pallet Quantity	7800

Product Assets

Literature - HDPJ High Density Jack Panels

