

Project:

Fixture Type:

Location

Contact:

Albin

Ceiling Mounted • Damp Location Listed PROGRESS LED

Description:

This ceiling fan offers a modern take on a traditional design that will find a perfect home in a variety of outdoor spaces and lifestyles. Five blades finished in a faux wood grain texture extend from a modern-style black center column. An LED light is encased in a crisp opal shade to illuminate a wellloved space meant to be lived-in and enjoyed.

Specifications:

- White Opal glass Bowl
- Five blades finished in a faux wood grain texture extend from a modern-style black center column.
- An LED light is encased in a crisp opal shade to illuminate a well-loved space meant to be lived-in and enjoyed.
- This ceiling fan offers a modern take on a traditional design that will find a perfect home in a variety of outdoor spaces and lifestyles.
- Ideal for any living room, great room, or bedroom.
- Perfect for any modern or transitional setting.
- Measures 54-inch width by 15-9/16-inch height.
- Uses one LED module that is included (24w max).
- Remote control included.
- Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- Dimmable to 10% brightness (See Dimming Notes)
- · Canopy covers a standard 4" recessed outlet box: 6.31 in W., 2.19 in ht., 6.31 in depth
- 80 in of wire supplied

Performance:

| Number of Modules | 1 |
|---------------------|------------------------------------|
| Input Power | 24 W |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 2,000/83 (LM-82) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 50000 (L70/TM-21) |
| Warranty | Limited Lifetime Warranty |
| Labels | cULus Damp Location Listed |
| | Meets California Title 24 JA8-2019 |
| | AC motor |

P250036-031-30






Dimensions:

Diameter: 54 in Height: 15-5/8 in

White Opal glass Bowl Width: 8-1/2 in Height: 2-5/8 in





Albin

Ceiling Mounted • Damp Location Listed PROGRESS LED

Dimming Notes:

P250036-031-30 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

| Devices IDEV009 |
|-----------------------|
| Lutron NTEVL-300 |
| Lutron DVELV-300P |
| Lutron DVCL-253P |
| Lutron TGCL-153-PH-WH |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P250036-031-30