

Project:

Fixture Type:

Location:

Contact:

Caleb

Ceiling downrod Mounted • Dry Location Listed

Description:

Caleb Collection 68-Inch 5-Blade Brushed Nickel AC Motor Transitional Ceiling Fan

Specifications:

- Canopy covers a standard 4" recessed outlet box: 5.875 in W., 2.375 in ht., 5.875 in depth
- Mounting Bracket
- 80 in of wire supplied

Performance:

Input Voltage	120 V
Input Frequency	60 Hz
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	Limited Lifetime warranty
Labels	UL Dry Location Listed
	AC motor





P2560-09WW

Dimensions:

Length: 68 in Diameter: 68 in Height: 18 in

ENERGYGUIDE	
Estimated Yearly Energy Cost \$177 (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (310) (3	Airflow 5,508 Cubic Feet Per Minute • The higher the airflow, the more air the fan will move • Airflow Efficiency. 91 Cubic Feet Per Minute Per Watt
All estimates based on typical use, excluding lights	ftc.gov/energy