

Project:		
Fixture Type:		
Location:		
Contact:		

One-Light LED Flush Mount

Ceiling mounted • Damp location listed PROGRESS LED



Description:

One-light 11 inch LED Flush Mount in Brushed Nickel features an etched Alabaster glass bowl. Fixtures are dimmable to 10 percent with Triac, phase forward or ELV dimmers. 3000K and 90 CRI.

Specifications:

- · Brushed Nickel (-009) (plated)
- · Steel Construction
- Etched Alabaster glass bowl
- 993 lumens 48 lumens/watt (delivered)
- 3000k color temperature, 90+ CRI
- · TM-21 54,000 hour life.
- · Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified
- · Meets California Title 24 JA8-2016

Performance:

Number of Modules	1
Input Power	21w
Input Voltage	120 V
Input Frequency	50/60 Hz
Lumens/LPW (Source)	1601/81 (LM-82)
Lumens/LPW (Delivered)	993/48 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	54,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-25 °C
Max. Operating Temp	25 ℃
Warranty	5 year warranty
Labels	ETL Damp location listed
	ENERGY STAR® qualified
	Meets California Title 24 JA8-2016



Images:



Dimensions:

Diameter: 11" Height: 5-1/2"





One-Light LED Flush Mount

Ceiling mounted • Damp location listed PROGRESS LED



P350001-009-30

Dimming Notes:

P350001 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron NTELV-300

Leviton 6672

Leviton 6674

Lutron AYLV-600P

Lutron NTLV-600

Lutron MAELV-600

Lutron N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.