

## Bezel LED

Flush-Mount Mounted • Damp Location Listed **PROGRESS LED**

### Description:

Bezel Collection 10" LED Flush Mount

### Specifications:

- Etched White Glass Shade
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 10.5 in W., 0.75 in ht., 10.5 in depth
- Mounting strap for outlet box included
- 6 in of wire supplied

### Performance:

Number of Modules	1
Input Power	17 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1,276/73 (LM-82)
Lumens/LPW (Delivered)	659/38.1 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30°C
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed Meets California Title 24 JA8-2016

# P350085-015-30



### Dimensions:

Diameter: 10-1/2 in  
 Height: 3-1/2 in

Etched White Glass Shade  
 Width: 9-3/4 in  
 Height: 2-1/2 in



# P350085-015-30

## Dimming Notes:

---

P350085-015-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## Dimming Controls:

---

Lutron\_Diva DVELV-300P

Lutron\_Nova T NTELV-300

Lutron\_Caseta

Lutron\_Ariadni AY-600P

Leviton\_Illumatech IPI06-1LZ

Lutron\_Lumea LG-603PG

Leviton\_SureSlide 6672

Leviton\_SureSlide 6674

Lutron\_Skylark Contour CTCL-153P

Lutron\_Diva DVCL-153P

Pass & Seymour\_Harmony DCL453PTCCCV6

Lutron\_Toggler TGCL-153P

Lutron\_Maestro MACL-153M

Lutron\_Ariadni AYL-600P

Lutron\_Maestro MA-600

Lutron\_Nova T NTLV-600

Lutron\_Maestro MAELV-600

Lutron\_spacer/system SPSELV-600

Leviton\_Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.