

Small Wall Lantern

Wall mounted • Wet location listed



Description:

The one-light wall lantern from the Belle LED Collection features nautical undertones and a cage reminiscent of industrial spaces that is ideal for both interior and exterior settings. This fixture is available in convertible ceiling/pendant and wall mount options. Small LED wall lantern. Textured Graphite finish.

Specifications:

- Textured Graphite (-136) (powder coat paint)
- Aluminum Construction
- Etched glass diffuser
- LED Module is replaceable (part # 93054049)
- Nautical undertones.
- Cage reminiscent of industrial spaces.
- Ideal for both interior and exterior spaces.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

| | |
|------------------------|--|
| Number of Modules | 1 |
| Input Power | 9w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 623/69.2 (LM-82) |
| Lumens/LPW (Delivered) | 401/50.9 (LM-79) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 60,000 (L70/TM-21) |
| FCC | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | 30 °C |
| Warranty | 5 year warranty |
| Labels | cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements for outdoor use only |

P5676-13630K9

Images:



Dimensions:

Width: 5-1/2"
Depth: 7-3/8"
Height: 10-5/8"
H/CTR: 3"

Glass
Width: 4-3/8"
Length: 4-3/8"
Height: 8-3/4"

P5676-13630K9

Dimming Notes:

P5676 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vierti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.