

P8108 SERIES 5.5 Inch LED New Construction And Remodel • Wet location listed



Description:

The P8108 delivers a solution for flush mount, for both residential and commercial markets. In addition, the P8108 is wet located, Title 24 - JA8 - 2016 and is a cost effective solution for fire rated application. The P8108 luminaire unites performance, cost and safety benefits.

Specifications:

- Antique Bronze finish.
- Diffused polycarbonate lens controls direct glare from the LEDs.
- Simple snap-in installation for J-Box.
- Die-cast aluminum construction with a powder coat paint finish.
- Can be installed in a 4" J-Box.
- Lumen output and distribution comparable to a 65W incandescent lamp.
- Requires a minimum 2" deep J-Box.
- Meets California Title 24 - JA8 - 2016.
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:


Input Power	11.75w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	685/58.3 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	50,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR® qualified
	Meets California Title 24 JA8-2016

Images: P8108-20-30K




Dimensions:

- (A) Outside Diameter: 5.5"
- (B) Height: 0-3/4"
- (C) Inside Diameter: 3.6"
- (D) Light Emitting Surface (LES): 3"
- (E) Overall Ht.: 2-3/4"



Included Mounting Options:

J-Box
Adapter



P8108-20-30K

Dimming Notes:

P8108 is designed to be compatible with many Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron AYCL-153P

Lutron AY-600

Lutron TGCL-153P

Lutron DVCL-153P

Leviton 6672

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.