

## Medium Track Head For AC LED Track

Ceiling mounted • Dry location listed



### P900000-028-27

#### Description:

P900000-028-27 Track Heads are compatible with the P900002-028-27 Track Kits. These AC LED Track Heads can be added to a track kit to provide more light when needed. They are 2700K color temperature with a 90+ CRI.

#### Specifications:

- Satin White (-028) (painted)
- Die Cast Aluminum construction
- Frosted glass lens
- 120V AC LED Track Head
- Additional LED track heads for the P900002-028-27 track kits
- Use when more track heads are needed for additional light
- Measures 2-7/8in w and 6-1/2in ht.
- 9.5w LED with 533 lumens, 90+ CRI and 2700K
- Flicker free dimming down to 10% with many Triac or reverse phase dimmers
- ENERGY STAR and JA8 Title 24 compliant
- Dimmable to 10% brightness (See Dimming Notes)
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

#### Performance:

Number of Modules	1
Input Power	9.5w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	
Lumens/LPW (Delivered)	533/55 (LM-79)
CCT	2700 K
CRI	90+ CRI
Life (hours)	50,000 (L70/TM-21)
FCC	
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cETLus Dry location listed ENERGY STAR® qualified Meets California Title 24 JA8-2016

#### Images:



#### Dimensions:

Width: 2-7/8"  
Depth: 2-3/4"  
Height: 6-1/2"

**P900000-028-27****Dimming Notes:**

---

P900000 is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron NTELV-300

Lutron Caseta

Lutron AY-600P

Lutron LG-603PG

Leviton 6672

Leviton 6674

Lutron AYCL-153P

Lutron DVCL-153P

Lutron MACL-153M

Lutron AYL-600P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.