

#### Project:

Fixture Type:

Location:

Contact:

P9062 Large LED Track Head

# Track mounted • Dry location listed PROGRESS LED

# Description:

The P9062 LED Track head with mesh back design is ideal for residential and light commercial applications. The P9062 has an integrated driver design for a small, sleek style.

## **Specifications:**

- White (-28) (painted)
- · Die Cast Aluminum construction
- Clear glass lens
- + Mesh back design
- Specular reflector.
- +  $\,$  P9051 power feed needed to electrify track.
- 48" and 96" track available (P9054 & P9058)
- Dimmable to 10% brightness (See Dimming Notes)
- ENERGY STAR<sup>®</sup> qualified
- Meets California Title 24 JA8-2016

## Performance:

Number of Modules	1
Input Power	10.4w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	620/59.6 (LM-79)
ССТ	2700 К
CRI	90+
Life (hours)	50,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cETLus Dry location listed
	ENERGY STAR <sup>®</sup> qualified
	Meets California Title 24 JA8-2016




#### Images:



## **Dimensions:**

(A) Width: 3.3"(B) Depth: 4"Height: 6.8"





# P9062 Large LED Track Head

Track mounted • Dry location listed PROGRESS LED



# **Photometrics:**

P9062-28-27K9

ELECTRICAL DATA	P9062-28-27K9	
Input Voltage	120 V	
Input Frequency	60 Hz	
Input Current	0.088 A	
Input Power	10.4	
Power Factor	>0.90	
THD	<20%	
EMI Filtering	FCC Title 47, Part 15 Class B	
Operating Temperature	-30 °C to 30° C	
Dimming	Yes*	
Over-voltage, over-current, short-circuit protected		
*See Dimming Notes for more information		

System Wattage: 10.4			
Fixture delivered lumens: 620			
Fixture E	fficacy: 59.6		
Spacing	Criteria: 0.35		
1 0			
	90°		
	75*		

LED Light Engine: 2700 K 90+ CRI

P9062-28-27K9

1000

2000

	CANDELA DISTRIBUTION			
90°	DEG	CAND	ELA	LUMENS
	0	2991		
75°	5	2650	220	
	15	662	207	
60°	25	270	130	
00	35	69	55	
	45	4	3	
45°	55	3	2	
45	65	1	1	
	75	1	1	
	85	0	0	
	90	0		

ZONAL I	UMEN SUM	MARY
Zone	Lumens	%Fixt
0-30	556	89.7
0-40	612	98.7
0-60	618	99.6
0-90	620	100.0
90-180	0	0.0
0-180	620	100.0



# P9062 Large LED Track Head

Track mounted • Dry location listed PROGRESS LED



# P9062-28-27K9

## **Dimming Notes:**

P9062 is designed to be compatible with many Triac/Forward Phase controls.

The following is a partial list of known compatible dimmer controls.

## **Dimming Controls**

Lutron NTELV-300
Lutron DVELV-300P
Lutron DVCL-253P
Lutron Caseta
Leviton 6681
Leviton 6672
Leviton 6674
Lutron AYLC-153P
Lutron TGCL-153PH
Lutron AYLV-600P
Lutron MAELV-600
Leviton AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.