

# PT102-6

by CMC  
Catalog ID: PT102-6

Compression connectors, Aluminum pin terminal

- Tinned copper rod factory crimped into an aluminum compression sleeve. Cavities are pre-filled with electrical joint compound and capped
- Pin terminals are widely used in clamp-type plated bronze connectors, common to pole-type transformers, disconnect switches, cutouts and lightning arrestors, to allow aluminum conductors to be connected. The transition from copper to aluminum is made within a sealed compression joint to assure protection from bi-metallic corrosion.



## Product Details

### General

Material	Aluminum
UPC	192663118991

### Dimensions

Equivalent Pin Size	2 Sol.
Length	9.875 in
Length - Pin	6 in

### Electrical Ratings

Voltage Rating	600 V
----------------	-------

### Conductor Related

Conductor - ACSR Str Size	1/0 AWG
Conductor Diameter - Maximum	0.398 in
Conductor Diameter - Minimum	0.336 in
Conductor Diameter Range	0.336 - 0.398



**CONNECTOR MANUFACTURING COMPANY**  
3501 Symmes Road  
Hamilton, Ohio 45015 - 1369  
513 - 860 - 4455(Press 2 for Customer Service and Sales)  
To email customer Service: [jrex @cmclugs.com](mailto:jrex@cmclugs.com)

