

1/2 in. 150 Degree Rigid/IMC Grounding Bushing, Feed-Through-Lug, Insulated

By Raco Catalog # 1222

1/2 in. 150 Degree Rigid/IMC Grounding Bushing, Feed-Through-Lug, Insulated



*Representative Image

Features

- Malleable iron construction ensures mechanical protection
- Zinc-electroplated for added corrosion protection
- Insuliner rated for 150° C
- Grounding Wire Capacity #14 Sol. #4 Str.
- UL and CSA Listed
- Available in trade sizes of 1/2 in. through 4 in.

General

Conduit Type Rigid/IMC
Connector Type Grounding

EU RoHS Indicator Contact Manufacturer

Fitting Type Bushings
Insulation Type Insulated
Material Malleable Iron
UPC 050169012222

Dimensions

Dimensions 0.578 in x 1.156 in x 1.656 in

Height 1.656 in
Length 0.578 in
Trade Size 1/2 in
Weight 0.073 lb
Width 1.156 in

Electrical Ratings

Grounding Wire Capacity #4 STR

Maximum

Grounding Wire Capacity #14 SOL

Minimum

Certifications And Compliance

Certified Listed UL Listed

CSA Certified

Industry Standard(s) UL 514B

Logistics

Carton Quantity 100
Minimum Pack Quantity 100
Pallet Quantity 32000

Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog Certifications - UL COC-E195975-1 Product Logo - Conduit SDS - HCC SDS Terms and Conditions - HCC Terms & Conditions

