

4-11/16 in. Square Box, 2-1/8 in. Deep (1) STAB-IT® Connector with Pigtail and Cable Management

By Raco Catalog # 252SCM

4-11/16 in. Square Box, Welded with STAB-IT® Connector, 2-1/8 in. Deep, Raised Ground, 8 in. #12 Solid Copper Pigtail, UBS, M Bracket, Cable Management Clip

Features

- Designed for quick installation of flex, MC, MCI, MCI-A, MC-PCS, AC, and HCF cable
- Accepts cable sizes from 14/2 up to 10/3 for most cable types
- 3 TIMES FASTER than traditional connectors
- + 4-11/16 in. sq. boxes are 2-1/8 in. deep and includes 1 STAB- $\rm IT^{\circledast}$ II connector
- Each STAB-IT® II connector accomodates three cables
- Includes built-in cable management clip, offering first means of support
- UL Listed for use without a plastic bushing (except for AC cable)
- Pre-installed 8 in. solid #12 pigtail for faster installation
- Suitable for use without a bonding jumper in circuits up to 600 volts
- Improved design allows each cable to easily be removed, allows connector to be reused
- Designed in USA

General

Application	Commercial
Bracket Type	No Bracket
Cable Clamps	1
Catalog Number	252SCM
Color	Gray
Drawn or Welded	Welded
Fire Resistance	Yes
Knockouts	(1) 1/2", (10) 1/2 - 3/4" TKO, (1)
	3/4 - 1" TKO
Material	Steel
Number of Gang(s)	2-Gang
Туре	Box
UPC	050169995471
Wiring System	Flex



Dimensions

Actual Depth	2.125 in
Cubic Capacity	42
Height	4.685 in
Raised Ground	Yes
Weight	1.306 lb
Width	4.85 in

Certifications And Compliance

Certified Listed cULus Listed

Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	1200

Product Assets

3D Models - 252SCM-3D Brochures - STAB-iT® Electrical Boxes Catalogs - RACO / TayMac / Bell Full Catalog Certifications - UL COC - E195978-5 Certifications - UL COC - E195978- 2 Installation Manuals - 119030_RA-356 Instr for web Literature - STAB-IT® II Cable Ranges Sales Drawings - 252SCM Customer Drawing SDS - HCC SDS Terms and Conditions - HCC Terms & Conditions Video - RACO: STAB-IT® II Boxes



©2024 Hubbell Incorporated. All rights reserved RACO-252SCM-SPEC-EN | REV 6/2024