

Concrete Ring, Welded, 3-1/2 in. Deep, Double Row 1/2 & 3/4 in. KO's

By Raco Catalog # 273

Concrete Ring, Welded, 3-1/2 in. Deep, Double Row 1/2 & 3/4 in. KO's



- Flat sides provide excellent contact for locknuts
- External ears are used to nail the ring to the wood form
- Top cover is removable for before-pour work
- · Ears on inside of box are for fixtures
- Waxed fixture ears prevent concrete from interfering with the threads
- · A variety of covers are available
- Cover plate must be orered separately with all RACO® concrete rings
- · Used in high-rise construction
- 49.3 cu. in. capacity
- Not designed for ceiling fan support, the maximum support load for a static fixture is 50 lbs

General

Color Gray Drawn or Welded Welded

EU RoHS Indicator Contact Manufacturer

Knockouts 1/2 in;3/4 in Material Steel

Type Concrete Ring UPC 050169002735 Wiring System Conduit



Dimensions

Cubic Capacity 43 cu.in Depth 3.5 in Fixture Lbs. 50 lb Height 4 in Weight 0.907 lb Width 4 in

Certifications And Compliance

Certified Listed **UL** Listed

Logistics

Carton Quantity 20

No Packaging Packaging Type

Pallet Quantity 1200

Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog Certifications - LEED Statement

Certifications - NEMA OS1

SDS - HCC SDS

Terms and Conditions - HCC Terms & Conditions

