


**RIGID BODIES AND ASSEMBLIES**

C Assembly  
N/A

C13



TRADE SIZE	CONDUIT	A	B	C	D	E TAPPED HOLES	F TAPPED HOLES	G THREADED HOLES	VOLUME	WEIGHT
3/4"	ALUMINUM	3.12	1.75	1.25	11.25	#5/16 UNC-2B	#5/16 UNC-2B	1/2-8 NPT	157.3	1.25
1"	ALUMINUM	3.50	2.00	1.50	12.50	#5/16 UNC-2B	#5/16 UNC-2B	1/2-8 NPT	175.0	1.40
1 1/4"	ALUMINUM	4.12	2.37	1.75	14.62	#5/16 UNC-2B	#5/16 UNC-2B	1/2-8 NPT	200.0	1.60
1 1/2"	ALUMINUM	4.37	2.50	1.87	15.37	#5/16 UNC-2B	#5/16 UNC-2B	1/2-8 NPT	210.0	1.65
2"	ALUMINUM	5.00	2.87	2.12	17.50	#5/16 UNC-2B	#5/16 UNC-2B	1/2-8 NPT	240.0	1.80
2 1/2"	ALUMINUM	5.62	3.25	2.37	19.62	#5/16 UNC-2B	#5/16 UNC-2B	1/2-8 NPT	270.0	2.00
3"	ALUMINUM	6.25	3.62	2.62	21.75	#5/16 UNC-2B	#5/16 UNC-2B	1/2-8 NPT	300.0	2.20
3 1/2"	ALUMINUM	6.87	4.00	2.87	23.87	#5/16 UNC-2B	#5/16 UNC-2B	1/2-8 NPT	330.0	2.40
4"	ALUMINUM	7.50	4.37	3.12	26.00	#5/16 UNC-2B	#5/16 UNC-2B	1/2-8 NPT	360.0	2.60



Catalog #: RLC250

**APPLICATIONS**

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.  
N/A

**PRODUCT FEATURES**

- Durable die cast aluminum construction
- Premium powder coat finish
- Includes NBR synthetic rubber gasket
- Stamped aluminum cover
- Combination head screw

**UL LISTED**

File E331564

**NEMA**

NEMA 3R rated

**NEC**

2014 NEC® compliant

**GENERAL PRODUCT INFORMATION**

Trade Size: 2-1/2 in.

**DRAWING DIMENSIONS**

- Dimension A: 13.46 in.
- Dimension B: 4.49 in.
- Dimension C: 3.98 in.
- Dimension D: 11.250 in.
- Dimension E: Tapped holes #5/16UNC-2B
- Thread Spec. F: 2-1/2-8NPT
- Dimension G: 2.459 in.

**PRODUCT MEASUREMENTS**

Cubic Inches (cm3): 157.3 (2578)

**PACKAGING**

- Package Type: Carton
- Ship Carton Qty.: 1
- Product UPC-A Labeled: Yes
- Weight (Lbs. Per/C): 370.00
- Ship Carton Length (in.): 14.13
- Ship Carton Width (in.): 5.00
- Ship Carton Height (in.): 5.25
- Ctn Weight (Lbs.): 3.70
- UPC Number: 092326213189
- I2of5: 30092326213180