


RIGID BODIES AND ASSEMBLIES

C Assembly
N/A

C13



TRADE SIZE	CONDUIT	A	B	C	D	E TAPPED HOLES	F TAPPED HOLES	G THREADED HOLES	VOLUME	WEIGHT
3/4"	ALUMINUM	2.12	1.18	1.20	4.00	#5/16UNC-2B	#5/16UNC-2B	1/2-20NPT	1.12	1.12
1"	ALUMINUM	2.31	1.25	1.25	4.50	#5/16UNC-2B	#5/16UNC-2B	1/2-20NPT	1.54	1.54
1 1/4"	ALUMINUM	2.50	1.38	1.38	5.00	#5/16UNC-2B	#5/16UNC-2B	1/2-20NPT	2.19	2.19
1 1/2"	ALUMINUM	2.69	1.50	1.50	5.50	#5/16UNC-2B	#5/16UNC-2B	1/2-20NPT	2.94	2.94
2"	ALUMINUM	3.08	1.63	1.63	6.00	#5/16UNC-2B	#5/16UNC-2B	1/2-20NPT	4.00	4.00
2 1/2"	ALUMINUM	3.47	1.76	1.76	6.50	#5/16UNC-2B	#5/16UNC-2B	1/2-20NPT	5.39	5.39
3"	ALUMINUM	3.86	1.89	1.89	7.00	#5/16UNC-2B	#5/16UNC-2B	1/2-20NPT	7.20	7.20
3 1/2"	ALUMINUM	4.25	2.02	2.02	7.50	#5/16UNC-2B	#5/16UNC-2B	1/2-20NPT	9.41	9.41
4"	ALUMINUM	4.64	2.15	2.15	8.00	#5/16UNC-2B	#5/16UNC-2B	1/2-20NPT	12.22	12.22



Catalog #: RLC350

APPLICATIONS

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.
N/A

PRODUCT FEATURES

- Durable die cast aluminum construction
- Premium powder coat finish
- Includes NBR synthetic rubber gasket
- Stamped aluminum cover
- Combination head screw

UL LISTED

File E331564

NEMA

NEMA 3R rated

NEC

2014 NEC® compliant

GENERAL PRODUCT INFORMATION

Trade Size: 3-1/2 in.

DRAWING DIMENSIONS

- Dimension A: 16.30 in.
- Dimension B: 5.55 in.
- Dimension C: 5.59 in.
- Dimension D: 13.687 in.
- Dimension E: Tapped holes #5/16UNC-2B
- Thread Spec. F: 3-1/2-8NPT
- Dimension G: 3.538 in.

PRODUCT MEASUREMENTS

Cubic Inches (cm3): 318.3 (5215)

PACKAGING

- Package Type: Carton
- Ship Carton Qty.: 1
- Product UPC-A Labeled: Yes
- Weight (Lbs. Per/C): 800.00
- Ship Carton Length (in.): 17.38
- Ship Carton Width (in.): 6.00
- Ship Carton Height (in.): 7.88
- Ctn Weight (Lbs.): 8.00
- UPC Number: 092326213202
- I2of5: 30092326213203