




## RIGID BODIES AND ASSEMBLIES

C Assembly  
N/A

C13



TRADE	CONDUIT	A	B	C	D	E TAPPED	F TAP	G THROAT Ø	H Ø	MINIMUM WIRE FILL	WEIGHT
1/2"	ALUMINUM	2.12	1.75	1.75	4.00	1.00	1.00	0.50	0.50	0.00	0.10
3/4"	ALUMINUM	2.31	1.94	1.94	4.25	1.12	1.12	0.56	0.56	0.00	0.12
1"	ALUMINUM	2.50	2.13	2.13	4.50	1.25	1.25	0.62	0.62	0.00	0.14
1 1/4"	ALUMINUM	2.87	2.50	2.50	5.00	1.50	1.50	0.75	0.75	0.00	0.18
1 1/2"	ALUMINUM	3.06	2.69	2.69	5.25	1.62	1.62	0.81	0.81	0.00	0.20
2"	ALUMINUM	3.43	3.06	3.06	6.00	1.87	1.87	0.93	0.93	0.00	0.24
2 1/2"	ALUMINUM	3.80	3.43	3.43	6.75	2.12	2.12	1.06	1.06	0.00	0.28
3"	ALUMINUM	4.17	3.80	3.80	7.50	2.37	2.37	1.18	1.18	0.00	0.32
3 1/2"	ALUMINUM	4.54	4.17	4.17	8.25	2.62	2.62	1.31	1.31	0.00	0.36
4"	ALUMINUM	4.91	4.54	4.54	9.00	2.87	2.87	1.43	1.43	0.00	0.40



Catalog #: RLC400

### APPLICATIONS

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.

N/A

### PRODUCT FEATURES

- Durable die cast aluminum construction
- Premium powder coat finish
- Includes NBR synthetic rubber gasket
- Stamped aluminum cover
- Combination head screw

### UL LISTED

File E331564

### NEMA

NEMA 3R rated

### NEC

2014 NEC® compliant

### GENERAL PRODUCT INFORMATION

Trade Size: 4 in.

### DRAWING DIMENSIONS

- Dimension A: 16.30 in.
- Dimension B: 5.55 in.
- Dimension C: 5.59 in.
- Dimension D: 13.687 in.
- Dimension E: Tapped holes #5/16UNC-2B
- Thread Spec. F: 4-8NPT
- Dimension G: 4.016 in.

### PRODUCT MEASUREMENTS

Cubic Inches (cm3): 323.0 (5293.0)

### PACKAGING

- Package Type: Carton
- Ship Carton Qty.: 1
- Product UPC-A Labeled: Yes
- Weight (Lbs. Per/C): 740.00
- Ship Carton Length (in.): 17.38
- Ship Carton Width (in.): 6.13
- Ship Carton Height (in.): 6.63
- Ctn Weight (Lbs.): 7.40
- UPC Number: 092326213219
- I2of5: 30092326213210