

SPT2010

by CMC
Catalog ID: SPT2010

Compression connectors, Shrouded Aluminum pin terminals

- Shroud accepts insulation of conductors.
- Tinned copper rod factory crimped into an aluminum compression sleeve. Cavities are pre-filled with electrical joint compound and capped.
- Pin terminals are widely used in clamp-type plated bronze connectors, common to pole-type transformers, disconnect switches, cutouts and lightning arrestors, to allow aluminum conductors to be connected. The transition from copper to aluminum is made within a sealed compression joint to assure protection from bi-metallic corrosion.



Product Details

General

Material	Aluminum
UPC	192663121632

Dimensions

Equivalent Pin Size	1/0 Sol.
Length	7 in
Length - Pin	4 in

Electrical Ratings

Voltage Rating	600 V
----------------	-------

Conductor Related

Conductor - ACSR Str Size	2/0
Conductor Diameter - Maximum	0.448 in
Conductor Diameter - Minimum	0.388 in
Conductor Diameter Range	0.388 - 0.448

Conductor Range

2/0 Str.;3/0 Comp.



CONNECTOR MANUFACTURING COMPANY

3501 Symmes Road
Hamilton, Ohio 45015 - 1369
513 - 860 - 4455(Press 2 for Customer Service and Sales)
To email customer Service: [jrex @cmclugs.com](mailto:jrex@cmclugs.com)

