TB300N008F1

by Acme Electric Catalog ID: TB300N008F1



ICT .300KVA 240X480-120 F1

- Encapsulated design protects core & coil assembly from potentially damaging contaminants
- Constructed with high quality silicon steel lamination to minimize core losses and increase efficiency
- Integrally molded terminal blocks with isolation barriers to prevent arc over
- Fuse blocks kits available and easily adaptable
- Series-parallel connecting links save wiring and labor costs

Product Details

General

Application	Acme's CE Series Industrial Control
Application	
	Transformers are especially designed to
	accommodate the momentary current inrush
	caused when electromagnetic components are
	energized without sacrificing secondary
	voltage stability beyond practical limits.The
	transformer's windings and internal terminations
	are encased in a durable thermoplastic end cap,
	protecting them from potentially damaging
	moisture, dirt and other ambient contaminants.
	Acme's TB Series transformers are dry-type,
	step-down transformers with the secondary
	control circuit isolated from the primary line
	circuit to assure maximum safety.
	circuit to assure maximum surety.

Color	Black
Secondary Voltage	120 V
UPC	047503010914

Dimensions

Dimensions	4.547 in x 4.5 in x 5.2897 in
Height	5.2897 in
Length	4.547 in
Weight	11.3 lb
Width	4.5 in

Electrical Ratings

Frequency Rating	50/60 Hz
Primary Voltage	240 X 480 V

Logistics

Carton Quantity 1
