TB500N006F2

by Acme Electric Catalog ID: TB500N006F2



ICT .500KVA 208,277 - 120 F2

- Encapsulated design protects core & coil assembly from potentially damaging contaminants
- Constructed with high quality silicon steel lamination to minimize core losses and increase efficiency
- Integrally molded terminal blocks with isolation barriers to prevent arc over
- Fuse blocks kits available and easily adaptable
- Series-parallel connecting links save wiring and labor costs

Product Details

General

| Application | Acme's CE Series Industrial Control |
|-------------|--|
| | Transformers are especially designed to |
| | accommodate the momentary current inrush |
| | caused when electromagnetic components are |
| | energized without sacrificing secondary |
| | voltage stability beyond practical limits. The |
| | transformer's windings and internal terminations |
| | are encased in a durable thermoplastic end cap, |
| | protecting them from potentially damaging |
| | moisture, dirt and other ambient contaminants. |
| | Acme's TB Series transformers are dry-type, |
| | step-down transformers with the secondary |
| | control circuit isolated from the primary line |
| | circuit to assure maximum safety. |
| | |

| Color | Black |
|-------------------|--------------|
| Secondary Voltage | 120 V |
| UPC | 047503010228 |

Dimensions

| Dimensions | 5.17 in x 5.25 in x 5.91 in |
|------------|-----------------------------|
| Height | 5.91 in |
| Length | 5.17 in |
| Weight | 19.2 lb |
| Width | 5.25 in |

Electrical Ratings

| Frequency Rating | 50/60 Hz |
|------------------|-----------|
| Primary Voltage | 208/277 V |

Logistics

| Carton Quantity 1 |
|-------------------|
|-------------------|