

by Acme Electric Catalog ID: TB75N006F4



ICT .075KVA 208,277 - 120 F4

- Encapsulated design protects core & coil assembly from potentially damaging contaminants
- Constructed with high quality silicon steel lamination to minimize core losses and increase efficiency
- Integrally molded terminal blocks with isolation barriers to prevent arc over
- Fuse blocks kits available and easily adaptable
- Series-parallel connecting links save wiring and labor costs

## **Product Details**

General

| Application       | Acme's TB Series Industrial Control Transformers<br>are especially designed to accommodate the<br>momentary current inrush caused when<br>electromagnetic components are energized<br>without sacrificing secondary voltage stability<br>beyond practical limits.The transformer's<br>windings and internal terminations are encased<br>in a durable thermoplastic end cap, protecting<br>them from potentially damaging moisture, dirt<br>and other ambient contaminants. Acme's TB<br>Series transformers are dry-type, step-down<br>transformers with the secondary control circuit<br>isolated from the primary line circuit to assure<br>maximum safety. |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color             | Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Secondary Voltage | 120 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| UPC               | 047503010303                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

## Dimensions

| Dimensions | 3.73 in x 3 in x 4.04 in |
|------------|--------------------------|
| Height     | 4.04 in                  |
| Length     | 3.73 in                  |
| Weight     | 53 lb                    |
| Width      | 3 in                     |

## **Electrical Ratings**

| Frequency Rating | 50/60 Hz  |
|------------------|-----------|
| Primary Voltage  | 208/277 V |

## Logistics

| Carton Quantity | 1   |
|-----------------|-----|
| Pallet Quantity | 168 |