

4000A 3-phase 600V Secondary Termination Enclosure

By Trinetics
Catalog # [63257641](#)



Trinetics multi-connection secondary termination enclosures provide safe, convenient, and aesthetically pleasing connection points for multiple services suitable for up to 600V. These enclosures are suitable for low voltage splicing or cable termination from the secondary side of a utility's transformer for multiple service feeds. Convertible 360-plus, patented, 5-point entry access enclosure with 2-point locking system and aluminum lay-in connectors for continuous current rating through 4000A.

Features

- Current rating for aluminum lay-in connectors is based on center feed.
- Current rating for copper bus is based on end-to-end feed.
- Two times the number of cables may be connected if front and back of bus are used.
- Please consult the factory or your local sales representative for any requirements not listed here.

Application

- Meets ANSI C57.12.28 standard
- NEMA 3R equivalent
- Lay-in connectors meets ANSI C119.6 specifications

General

| | |
|-----------------|--|
| Catalog Number | 63257641 |
| Color | Munsell Green |
| Connector Type | Aluminum 2-set screw lay-in Connectors |
| Enclosure Style | 5 point access with 2 point latch |
| Number Of Ports | 22 |

Dimensions

| | |
|--------|------|
| Depth | 36 |
| Height | 0 in |
| Length | 0 in |
| Width | 0 in |

Electrical Ratings

| | |
|--|--------|
| Current / Amperage Rating | 4000 A |
| Maximum Current Rating Amps Continuous | 4000 |

Conductor Related

| | |
|------------|----------|
| Wire Range | 1/0-1000 |
|------------|----------|

Certifications And Compliance

| | |
|--------------------------|---|
| Buy America(n) Qualified | TAA Compliant (All status valid till December 2024) |
|--------------------------|---|

Product Assets

[Catalogs - Secondary Termination Enclosures](#)
[Catalogs - Trinetics® Metal Sectionalizing Cabinets and Primary Pedestals](#)
[Specifications - 63257641](#)