



Aluminum Compression Terminal for #6 AL/CU, #4 sol CU, #6 6/1 ACSR

by ANDERSON
Catalog ID: VAUL612

Aluminum Compression Terminal (Replaces ESP-AD, AMS, and ALM Series)for #6 AL/CU, #4 sol CU, #6 6/1 ACSR, 1 HOLE

- Connectors are prefilled with rubber compatible inhibitor and sealed with color coded end caps.

* Representative image

Product Details

General

Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
Die Index	5/8 (243, BG)
Die Size	*See Resources / Downloads for die selection and installation instructions
Material	Aluminum
Material - Body	Aluminum
Number of Pad Holes	1
Plating	No
Style	Impact Extruded
UPC	096359334965

Dimensions

Diameter - Pad Bolt	0.5 in
Weight	0.098 lb

Conductor Related

Conductor Compatibility	ACSR-Turkey-6-6/1;AAC-Peachbell-6-7;AAAC 6201 Alloy-Akron-30.58-6/18
Conductor Diameter (VersaCrimp) - Maximum	0.204 in
Conductor Diameter (VersaCrimp) - Minimum	0.146 in

Certifications and Compliance

UL Listed	No
-----------	----

Logistics

Carton Quantity	200 EA
-----------------	--------

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscshubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com