



# Aluminum Compression Terminal for #6 AL/CU, #4 sol CU, #6 6/1 ACSR

by ANDERSON  
Catalog ID: VAULH612

Aluminum Compression Terminal for #6 AL/CU, #4 sol CU, #6 6/1 ACSR, 1 HOLE

- Connectors are prefilled with rubber compatible inhibitor and sealed with color coded end caps.

\* Representative image

## Product Details

### General

Crimp Method	VERSAtile™ (Accommodates Conventional And Anderson Tools)
Die Index	840 (249)
Die Size	*See Resources / Downloads for die selection and installation instructions
Material	Aluminum
Material - Body	Aluminum
Number of Pad Holes	1
Plating	No
Style	Impact Extruded
UPC	096359335078

### Dimensions

Diameter - Pad Bolt	0.5 in
Weight	0.196 lb

### Conductor Related

Conductor Compatibility	ACSR-Turkey-6-6/1;AAC-Peachbell-6-7;AAAC 6201 Alloy-Akron-30.58-6/18
Conductor Diameter (VersaCrimp) - Maximum	0.204 in
Conductor Diameter (VersaCrimp) - Minimum	0.146 in

### Certifications and Compliance

UL Listed	No
-----------	----

### Logistics

Carton Quantity	100 EA
-----------------	--------

For further technical assistance, please contact us

**Domestic Customer Service**

Hubbell Power Systems  
210 N. Allen Centralia, MO 65240 USA  
Phone: (573) 682-5521  
Fax: (573) 682-8475  
Email: [hpscshubbell.com](mailto:hpscshubbell.com)

**International Customer Service**

Phone: +1-573-682-5521  
Fax: +1-573-682-8516  
Email: [hpsintlcs@hubbell.com](mailto:hpsintlcs@hubbell.com)