

# Terminal, Aluminum Weldment

by ANDERSON  
Catalog ID: W2CF129D

Terminal, Aluminum Weldment, Two Cables to Flat, cable range 1.209-1.245 Pad: 4 hole, 4 in. TERMINAL, AL WLD (2) 1.196-1.245 IN D PD

- 90° pad orientation available



\* Representative image

## Product Details

### General

Material	Aluminum
Number of Bolt Holes	4
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Terminal, Aluminum Weldment
UPC	096359353126

### Dimensions

Angle - Pad	180 °
Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	2.646 lb
Width - Pad	4 in

### Electrical Ratings

Maximum Current Rating Amps Continuous	0
--	---

### Conductor Related

Conductor Compatibility	ACSR-Ortolan-1033.5-45/7;ACSR-Curlew-1033.5-54/7;AAC-Marigold-1113-61
Conductor Diameter - Maximum	1.245 in
Conductor Diameter - Minimum	1.209 in

Conductor Diameter Range	1.209 - 1.245
Conductor Type	<ul style="list-style-type: none"><li>• AAC</li><li>• ACSR</li></ul>

**For further technical assistance, please contact us**

**Domestic Customer Service**

Hubbell Power Systems  
210 N. Allen Centralia, MO 65240 USA  
Phone: (573) 682-5521  
Fax: (573) 682-8475  
Email: [hpscsc@hubbell.com](mailto:hpscsc@hubbell.com)

**International Customer Service**

Phone: +1-573-682-5521  
Fax: +1-573-682-8516  
Email: [hpsintlcs@hubbell.com](mailto:hpsintlcs@hubbell.com)