



Terminal, Aluminum Weldment

by ANDERSON
Catalog ID: W2CF97C

Terminal, Aluminum Weldment, Two Cables to Flat, cable range 0.891-0.93 Pad: 4 hole, 3 in. TERMINAL, AL WLD (2) .891-.930 IN C PAD

- 90° pad orientation available



* Representative image

Product Details

General

Material	Aluminum
Number of Bolt Holes	4
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Terminal, Aluminum Weldment
UPC	096359340201

Dimensions

Angle - Pad	180 °
Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	1.078 lb
Width - Pad	3 in

Electrical Ratings

Maximum Current Rating Amps Continuous	0
--	---

Conductor Related

Conductor Compatibility	ACSR-Parakeet-556.5-24/7;ACSR-Dove-556.5-26/7;ACSR-Swift-636-36/1;AAC-Meadowsweet-600-37;AAC-Orchid-636-37
Conductor Diameter - Maximum	0.93 in
Conductor Diameter - Minimum	0.891 in

Conductor Diameter Range	0.891 - 0.93
Conductor Type	<ul style="list-style-type: none">• AAC• ACSR

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscsc@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com