Hubbell-Pro Residential AUTOGUARD® Self-Test GFCI Receptacle, 20A, Light Almond

By Hubbell Wiring Device-Kellems Catalog # GF20LA

HUBBELLPRO, GFCI, 20A, Light Almond



- · Ground fault EOL indicator
- Comprehensive diagnostics
- · No power at face if reverse wired
- · Automatic self-grounding staple makes installation ease

Application

• Heavy Duty Commercial Grade

Performance

- Electrical Amperage 15A/20A, 20A Feed Thru
- Electrical Max. Interrupting Capacity 10,000A
- Electrical Voltage 120V AC +10% 15% (102V to 132V)
- Environmental Maximum Humidity 0.95
- Environmental Operating Temperature -35°C to 66°C or -30°F to 150°F.

General

Catalog Number GF20LA Color Light Almond

EU RoHS Indicator Yes

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Item Type **Decorator Duplex** Material Thermoplastic Material - Mounting Hardware Screw Mounting

OEM Brand Name

Number Of Poles

Hubbell Wiring Device-Kellems Specifications • Codes - Meets all NEC® and

2-Pole

CEC requirements • Frequency - 60 Hz

• Trip Level - 4 to 6 mA

• Trip Time - .025 second nominal

Туре Standard UPC 883778450631



Dimensions

Display Size Standard Sized Product

Electrical Ratings

Connectivity Back and Side Wired Screw

Terminals

Current / Amperage Rating 20 A Current Rating 20 A

Single Phase Phase 125 VAC Voltage Rating Voltage Rating Description 125 VAC 2500 Wattage

Conductor Related

Number Of Wires 3-Wire Grounding #14 AWG to #12 AWG Wire Size

Certifications And Compliance

Industry Standard(s) Meets UL498 For Receptacles

Nema Rating 5-20R

Logistics

10 Carton Quantity

Product Assets

Catalogs - WDK Catalog Full 2024

Engineering Drawing - GF20LA AutoCAD Drawing Installation Manuals - WIRING_PD2490_INSTALLINST

Literature - PULP & PAPER SOLUTIONS

Literature - Pulp & Paper Solutions Literature - Residential Catalog

Literature - HUBBELLPRO Ground Fault Receptacles Sales Drawings - WDK GF20LA DRAWING PDF

Specifications - GF20LA

Warranty - Industrial & Commercial Products

