



Power Quality Products, SPIKESHIELD Wired-In Branch Panel Protection, 100KA, 3PH 600V, with Filter

By Hubbell Wiring Device-Kellems
Catalog # [HBL1W100C](#)



Power Quality Products, SPIKESHIELD Wired-In Branch Panel Protection, 100KA, 3PH 600V, with Filter

Application

Surface Mount Brick with Leads

General

EU RoHS Indicator	No
Environmental Conditions	Indoor and Outdoor
Indicator(s) Type	Green Status LED, Audible Alarm
Item Type	Wired-In Branch Panel Protection
Material	Steel
Material - Mounting Hardware	Mounting Screws
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	-40 Degrees F to 149 Degrees F (-40 C to 65 C)
Performance	<ul style="list-style-type: none"> • Electrical - Diagnostics - Green Status LED's, Audible Alarm, Dry Contacts • Electrical - Surge Current per Phase - 100kA • Environmental - Operating Temperature - -40°F to 140°F (-40°C to 60°C) • Mechanical - Terminal Accommodation - #10 AWG 18.0" Wire Leads
Response Time	5
Series	Wired-In Panels
Type	100kA
UPC	783585120911

Dimensions

Display Size 100kA Peak

Electrical Ratings

Connectivity	Leads
Frequency Rating	60 Hz
Phase	Three Phase
Voltage Rating	Delta 600 VAC
Voltage Rating Description	600 VAC Delta

Certifications and Compliance

Industry Standard(s) cULus UL1449-3Rd Edition Type 2 Spd

Product Assets

- [Catalog Page - Wiring N-6 Catalog page](#)
- [Catalogs - Wiring Full Catalog](#)
- [Engineering Drawing - HBL1W100C AutoCAD Drawing](#)
- [Literature - Healthcare Product Solutions](#)
- [Literature - SpikeShield® Power Quality Surge Protective Devices](#)
- [Literature - Industrial Solutions](#)
- [Sales Drawings - WDK_HBL1W100C_DRAWING_PDF](#)
- [Warranty - SPD Series: 320kA, 160kA, 100kA, 120kA, 80mKA & 50kA](#)

Related Products

- [HBL1SA40 - Surge Arrestors, 40KA, 600V AC, Three Delta, Type 1](#)
- [HBL1P160B - Surge Protective Devices, Panel, 160KA Peak Capacity, Delta 600V AC, 3-Pole 4-Wire Grounding](#)



A proud member of the Hubbell Family.