

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Receptacle, 30A 480V AC, 2-Pole 3- Wire Grounding, Watertight

By Hubbell Wiring Device-Kellems  
Catalog # [HBL330R7W](#)

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Female, Receptacle, 30A 480V AC, 2-Pole 3- Wire Grounding, Terminal Screws, Red, Watertight

Features

- Corrosion-resistant self-closing gasketed cover
- Insulated non-metallic housing
- Color coded housings for easy identification

Application

- High Ampacity Watertight Connections

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - 3000V AC
- Electrical - Max. Working Voltage - 600V RMS
- Electrical - Temperature Rise - Max. 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%
- Environmental - Flammability - HB or better per UL 94 or CSA C22.2 No. 0.17
- Environmental - Ingress Protection - IP67 Suitability
- Environmental - Moisture Resistance - Watertight per IEC 60309-1
- Environmental - Operating Temperatures - Maximum Continuous 75°C
- Minimum - 40°C w/o impact
- Mechanical - Impact Resistance - Per CSA C22.2 No.182.1 /UL1682
- Mechanical - Product Identification - Identification and ratings are a permanent part of the device housing
- Mechanical - Terminal Identification - Terminals identified in accordance with North American and IEC conventions

General

Catalog Number	HBL330R7W
Color	Red
EU RoHS Indicator	Yes
Environmental Conditions	Watertight
Item Type	Single Flanged



Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Series	HBL Heavy Duty
Specifications	<ul style="list-style-type: none"><li>• Cover - Reinforced Thermoplastic Polyester</li><li>• Cover Screw - Nickel-plated brass</li><li>• Gaskets - Solid Neoprene</li><li>• Housing - Zytel® 101 Nylon</li><li>• Mounting Flange - Zytel® 101 Nylon</li></ul>
Style	Standard Service
Type	Watertight Receptacle
UPC	783585403632

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A
Phase	Single Phase
Voltage Rating	480 VAC
Voltage Rating Description	480 VAC
Wattage	14400

Conductor Related

Number Of Wires	3-Wire
Wire Size	#12 AWG to #8 AWG

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none"><li>• CSA StandardC22.2 No. 182.1</li></ul>
----------------------	---

Nema Rating

• UL Classified to IEC 60309-1  
IEC 60309-2

• UL Listed, File E146032

Non-NEMA

Logistics

Carton Quantity

10

Product Assets

- Catalog Page - [WDK G-10 Catalog Page](#)
- Catalogs - [WDK Catalog Full 2024](#)
- Engineering Drawing - [HBL330R7W AutoCAD Drawing](#)
- Installation Manuals - [WIRING\\_PD1304\\_INSTALLINST](#)
- Literature - [PULP & PAPER SOLUTIONS](#)
- Literature - [IEC Pin & Sleeve Devices](#)
- Literature - [Pulp & Paper Solutions](#)
- Sales Drawings - [WDK\\_HBL330R\\_DRAWING\\_PDF](#)
- Specifications - [Wiring HBL330R7W Specification Sheet](#)
- Warranty - [Industrial & Commercial Products](#)

