



Surge Protective Devices, Panel, 160KA Peak Capacity, 120/240V AC, 3-Pole 4-Wire Grounding, With Disconnect

By Hubbell Wiring Device-Kellems
Catalog # [HBL3P160DB](#)



Surge Protective Devices, Panel, 160KA Peak Capacity, 120/240V AC, 3-Pole 4-Wire Grounding, With Disconnect

Features

- Improved performance through the use of a low impedance bus-bar design
- Replaceable surge protection modules
- Surge counter included in all units
- NEMA 1 enclosure
- LED and audible alarm status indicator

General

EU RoHS Indicator	Contact Manufacturer
Series	Panels
Type	160kA
UPC	783585570075

Electrical Ratings

Voltage Rating	<ul style="list-style-type: none">• Single Phase 120 VAC• Single Phase 240 VAC
Voltage Rating Description	120/240 VAC Single Phase

Product Assets

[Catalog Page - Wiring N-4 Catalog page](#)
[Catalogs - Wiring Full Catalog](#)
[Installation Manuals - WIRING_P120 P160 P320 INSTALLATION INSTRUCTIONS_INSTALLINST](#)
[Literature - SpikeShield® Power Quality Surge Protective Devices](#)
[Sales Drawings - WDK_HBL3P_DRAWING_PDF](#)
[Warranty - SPD Series: 320kA, 160kA, 100kA, 120kA, 80MkA & 50kA](#)

Related Products

[HBLSDSA36 - Surge Protective Devices, SPIKESHIELD Panel Style, 36KA Single Phase](#)
[HBL3P320DB - Surge Protective Devices, Panel, 320KA Peak Capacity, 120/240V AC, 3-Pole 4-Wire Grounding, With Disconnect](#)
[HBL3W50 - Surge Protective Devices, SPIKESHIELD Surface Mount Block, 50KA, 120/240V AC](#)
[HBL3W100C - Surge Protective Devices, SPIKESHIELD Surface Mount Block, 100KA, 120/240V AC](#)
[HBL3P120C - Surge Protective Devices, Panel, 120KA Peak Capacity, 120/240V AC, 3-Pole 4-Wire Grounding](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
WDK-HBL3P160DB-SPEC-EN | REV 5/2023