

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male, Flanged Inlet, 30A 125/250V, 3-Pole 4- Wire Grounding, Watertight

By Hubbell Wiring Device-Kellems
Catalog # [HBL430B12W](#)

Heavy Duty IEC Pin and Sleeve Industrial Grade Male Flanged Inlet, 30A 125/250V, 3-Pole 4-Wire Grounding, Terminal Screws, Watertight

Features

- Rugged one-piece housing
- Thermoset polyester contact carrier
- Solid one-piece pins for reliable electrical contact

Application

- High Ampacity Watertight Connections

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - 3000V AC
- Electrical - Max. Working Voltage - 600V RMS
- Environmental - Flammability - HB or better per UL 94 or CSA C22.2 No. 0.17
- Environmental - Ingress Protection - IP67 Suitability
- Environmental - Moisture Resistance - Watertight per IEC 60309-1.
- Environmental - Operating Temperatures - Maximum Continuous 75°C
- Minimum - 40°C w/o impact
- Mechanical - Cord Grip Retention - Per CSA C22.2 No.182.1 /UL1682
- Mechanical - Product Identification - Identification and ratings are a permanent part of the device housing
- Mechanical - Terminal Identification - Terminals identified in accordance with North American and IEC conventions

General

Catalog Number	HBL430B12W
Color	Orange
EU RoHS Indicator	Yes
Environmental Conditions	Watertight
Insulation	Insulated Body
Item Type	Single Flanged
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting



Number Of Poles	3-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Series	HBL Heavy Duty
Specifications	<ul style="list-style-type: none">• Contact Carrier - High-Impact Thermoset• Gaskets - Solid Neoprene• Housing - Zytel® 101 Nylon• Locking Ring - Reinforced Thermoplastic Polyester• Phase Pins - Brass
Style	Standard Service
Temperature Rating	Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact
Type	Watertight Inlet
UPC	783585404455

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A
Dielectric Strength	Withstands 3000V Minimum in
Phase	Single Phase
Voltage Rating	125/250 VAC
Voltage Rating Description	125/250 VAC
Wattage	7500

Conductor Related

Number Of Wires	4-Wire
Wire Size	#12 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none">• CSA Certified File LR280C
----------------------	---

Nema Rating	<ul style="list-style-type: none">UL Classified to IEC 60309-1 IEC 60309-2UL Listed, File E146032	Catalogs - WDK Catalog Full 2024
	Non-NEMA	Engineering Drawing - HBL430B12W AutoCAD Drawing
Logistics		Installation Manuals - WIRING_PD1304_INSTALLINST
		Literature - Advantage™ Series Switch-Rated IEC Pin & Sleeve Devices
Carton Quantity	10	Literature - IEC Pin & Sleeve Devices
		Literature - PULP & PAPER SOLUTIONS
Literature - Pulp & Paper Solutions		
Sales Drawings - WDK_HBL430B_DRAWING_PDF		
Specifications - Wiring HBL430B12W Specification Sheet		
Warranty - Industrial & Commercial Products		
Video - Advantage Series Switch-Rated Pin & Sleeve		
Product Assets		
Catalog Page - WDK G-6 Catalog Page		
Catalog Page - WDK G-10 Catalog Page		