

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male, Flanged Inlet, 30A 3-Phase Delta 600V AC, 3-Pole 4-Wire Grounding, Watertight

By Hubbell Wiring Device-Kellems  
Catalog # [HBL430B5W](#)

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male, Flanged Inlet, 30A 3-Phase Delta 600V AC, 3-Pole 4-Wire Grounding, Terminal Screws, Black, Watertight

Features

- Rugged one-piece housing
- Thermoset polyester contact carrier
- Solid one-piece pins for reliable electrical contact

Application

- High Ampacity Watertight Connections

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - 3000V AC
- Electrical - Max. Working Voltage - 600V RMS
- Environmental - Flammability - HB or better per UL 94 or CSA C22.2 No. 0.17
- Environmental - Ingress Protection - IP67 Suitability
- Environmental - Moisture Resistance - Watertight per IEC 60309-1.
- Environmental - Operating Temperatures - Maximum Continuous 75°C
- Minimum - 40°C w/o impact
- Mechanical - Cord Grip Retention - Per CSA C22.2 No.182.1 /UL1682
- Mechanical - Product Identification - Identification and ratings are a permanent part of the device housing
- Mechanical - Terminal Identification - Terminals identified in accordance with North American and IEC conventions

General

Catalog Number	HBL430B5W
Color	Black
EU RoHS Indicator	Yes
Environmental Conditions	Watertight
Insulation	Insulated Body
Item Type	Single Flanged
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting



Number Of Poles	3-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Series	HBL Heavy Duty
Specifications	<ul style="list-style-type: none"><li>• Contact Carrier - High-Impact Thermoset</li><li>• Gaskets - Solid Neoprene</li><li>• Housing - Zytel® 101 Nylon</li><li>• Locking Ring - Reinforced Thermoplastic Polyester</li><li>• Phase Pins - Brass</li></ul>

Style	Standard Service
Temperature Rating	Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact
Type	Watertight Inlet
UPC	783585404462

Dimensions

Display Size	Standard Sized Product
--------------	------------------------

Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A
Dielectric Strength	Withstands 3000V Minimum in
Phase	Three Phase
Voltage Rating	3 Phase 600 VAC
Voltage Rating Description	3 Phase 600 VAC
Wattage	18000

Conductor Related

Number Of Wires	4-Wire
Wire Size	#12 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none"><li>• CSA Certified File LR280C</li></ul>
----------------------	---

Nema Rating	<ul style="list-style-type: none"><li>UL Classified to IEC 60309-1 IEC 60309-2</li><li>UL Listed, File E146032</li></ul>	Engineering Drawing - HBL430B5W AutoCAD Drawing Installation Manuals - WIRING_PD1304_INSTALLINST Literature - Advantage™ Series Switch-Rated IEC Pin & Sleeve Devices Literature - IEC Pin & Sleeve Devices Literature - PULP & PAPER SOLUTIONS Literature - Pulp & Paper Solutions Literature - IEC Pin & Sleeve Devices Sales Drawings - WDK_HBL430B_DRAWING_PDF Specifications - Wiring HBL430B5W Specification Sheet Warranty - Industrial & Commercial Products Video - Advantage Series Switch-Rated Pin & Sleeve
	Non-NEMA	
Logistics		
Carton Quantity	10	
Product Assets		
<a href="#">Catalog Page - WDK G-6 Catalog Page</a> <a href="#">Catalog Page - WDK G-10 Catalog Page</a> <a href="#">Catalogs - WDK Catalog Full 2024</a>		



A Hubbell brand