



# Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5- 15R, Ivory

By Hubbell Wiring Device-Kellems  
Catalog # [HBL5260ISA](#)



Surge Protective Devices, SPIKESHIELD TVSS Duplex  
Receptacle with Light, 15A 125V, 5-15R, Ivory

## Application

Decorator Duplex

## General

|                              |  |
|------------------------------|--|
| Color                        | Ivory  |
| Environmental Conditions     | Indoor Dry Unless Protected By Additional Means  |
| Indicator(s) Type            | None   |
| Item Type                    | Surge Protection Receptacles   |
| Material                     | Composite  |
| Material - Mounting Hardware | Mounting Screws  |
| OEM Brand Name               | Hubbell Wiring Device-Kellems  |
| Operating Temperature        | 32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)  |
| Outlet                       | Straight Blade   |
| Performance                  | <ul style="list-style-type: none"> <li>• Electrical - Protection Modes - Normal and Common Modes</li> <li>• Electrical - Response Time - Approximately 5 ns</li> <li>• Electrical - Transient Suppression - Peak Energy (10 X 100 <math>\mu</math>s), Peak Current (8 X 20 <math>\mu</math>s)</li> <li>• Electrical - Voltage - 120V AC + 10% - 15%</li> <li>• Environmental - Flammability - UL 94V-2</li> <li>• Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)</li> </ul> |
| Response Time                | 5  |
| Series                       | Specification Grade  |
| Type                         | Duplex   |
| UPC                          | 783585060996   |

## Dimensions

|              |          |
|--------------|----------|
| Display Size | Standard |
|--------------|----------|

## Electrical Ratings

|                            |                 |
|----------------------------|-----------------|
| Amperage Rating            | 15 A            |
| Connectivity               | Terminal Screws |
| Current / Amperage Rating  | 15 A            |
| Current Rating             | 15 A            |
| Frequency Rating           | 60 Hz           |
| Phase                      | Single Phase    |
| Voltage Rating             | 125 V           |
| Voltage Rating Description | 125 V           |

## Certifications and Compliance

|                      |   |
|----------------------|---|
| Industry Standard(s) | <ul style="list-style-type: none"> <li>• CSA Certified to Specification C22.2 No. 42</li> <li>• Listed to UL Standards 498</li> <li>• UL Listed File E2186</li> </ul> |
|----------------------|---|

|             |       |
|-------------|-------|
| Nema Rating | 5-15R |
|-------------|-------|

## Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

## Product Assets

- [Catalog Page - Wiring N-13 Catalog page](#)
- [Catalogs - Wiring Full Catalog](#)
- [Engineering Drawing - HBL5260ISA AutoCAD Drawing](#)
- [Installation Manuals - WIRING\\_PD1152\\_INSTALLINST](#)
- [Literature - SpikeShield® Power Quality Surge Protective Devices](#)
- [Literature - Residential Product Guide](#)
- [Literature - Residential Catalog](#)
- [Sales Drawings - WDK\\_HBL5260\\_DRAWING\\_PDF](#)
- [Warranty - Industrial & Commercial Products](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.  
WDK-HBL5260ISA-SPEC-EN | REV 4/2023