



Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5- 15R, Office White

By Hubbell Wiring Device-Kellems
Catalog # [HBL5260OWSA](#)



Surge Protective Devices, SPIKESHIELD TVSS Duplex
Receptacle with Light, 15A 125V, 5-15R, Office White

Application

Decorator Duplex

General

| | |
|------------------------------|--|
| Color | Office White |
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means |
| Indicator(s) Type | None |
| Item Type | Surge Protection Receptacles |
| Material | Composite |
| Material - Mounting Hardware | Mounting Screws |
| OEM Brand Name | Hubbell Wiring Device-Kellems |
| Operating Temperature | 32 Deg F to 140 Deg F (0 Deg C to 60 Deg C) |
| Outlet | Straight Blade |
| Performance | <ul style="list-style-type: none"> • Electrical - Protection Modes - Normal and Common Modes • Electrical - Response Time - Approximately 5 ns • Electrical - Transient Suppression - Peak Energy (10 X 100 μs), Peak Current (8 X 20 μs) • Electrical - Voltage - 120V AC + 10% - 15% • Environmental - Flammability - UL 94V-2 • Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C) |
| Response Time | 5 |
| Series | Specification Grade |
| Type | Duplex |
| UPC | 783585061009 |

Dimensions

| | |
|--------------|----------|
| Display Size | Standard |
|--------------|----------|

Electrical Ratings

| | |
|----------------------------|-----------------|
| Amperage Rating | 15 A |
| Connectivity | Terminal Screws |
| Current / Amperage Rating | 15 A |
| Current Rating | 15 A |
| Frequency Rating | 60 Hz |
| Phase | Single Phase |
| Voltage Rating | 125 V |
| Voltage Rating Description | 125 V |

Certifications and Compliance

| | |
|----------------------|---|
| Industry Standard(s) | <ul style="list-style-type: none"> • CSA Certified to Specification C22.2 No. 42 • Listed to UL Standards 498 • UL Listed File E2186 |
|----------------------|---|

| | |
|-------------|-------|
| Nema Rating | 5-15R |
|-------------|-------|

Logistics

| | |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Product Assets

- [Catalog Page - Wiring N-13 Catalog page](#)
- [Catalogs - Wiring Full Catalog](#)
- [Engineering Drawing - HBL5260OWSA AutoCAD Drawing](#)
- [Installation Manuals - WIRING_PD1152_INSTALLINST](#)
- [Literature - SpikeShield® Power Quality Surge Protective Devices](#)
- [Sales Drawings - WDK_HBL5260_DRAWING_PDF](#)
- [Warranty - Industrial & Commercial Products](#)



