

**HUBBELL**  
Wiring Device-Kellems

## **TVSS Duplex Receptacle with Light and Alarm, 15A 125V, 5-15R, Almond**

By Hubbell Wiring Device-Kellems  
Catalog # [HBL5262ALSA](#)

TVSS Duplex Receptacle with Light and Alarm, 15A 125V, 5-15R,  
Almond



## Features

- 
- 
- 
- 

## General

Application	Decorator Duplex with Light and Alarm
Catalog Number	HBL5262ALSA
Color	Almond
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED and Audible Alarm
Item Type	Surge Protection Receptacles
Material	Composite
Material - Mounting Hardware	Mounting Screws
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade
Performance	Electrical - Protection Modes - Normal and Common Modes
	Electrical - Response Time - Approximately 5 ns
	Electrical - Transient Suppression - Peak Energy (10 X 100 Qs), Peak Current (8 X 20 Qs)
	Electrical - Voltage - 120V AC + 10% - 15%
	Environmental - Flammability - UL 94V-2
	Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)
Response Time	5
Series	Specification Grade
Type	Duplex
UPC	783585436081

## Dimensions

Display Size	Standard
--------------	----------

## Electrical Ratings

Amperage Rating	15 A
Connectivity	Terminal Screws
Current / Amperage Rating	15 A
Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V

## Certifications And Compliance

Industry Standard(s)	CSA Certified to Specification C22.2 No. 42
	Listed to UL Standards 498
	UL Listed File E2186
Nema Rating	5-15R

## Logistics

Carton Quantity	10
-----------------	----

## Product Assets

[Engineering Drawing - HBL5262ALSA AutoCAD Drawing](#)  
[Installation Manuals - WIRING\\_PD1152\\_INSTALLINST Literature - SpikeShield® Power Quality Surge Protective Devices](#)  
[Sales Drawings - WDK\\_HBL5262\\_DRAWING\\_PDF](#)  
[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
WDK-HBL5262ALSA-SPEC-EN | REV 6/2024