

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light and Alarm, 15A 125V, 5-15R, Blue

By Hubbell Wiring Device-Kellems Catalog # HBL5262ISA

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light and Alarm, 15A 125V, 5-15R, Blue



Application

Decorator Duplex with Light and Alarm

General

Color **Environmental Conditions**

By Additional Means Indicator(s) Type LED and Audible Alarm Item Type Surge Protection Receptacles Material Composite

Material - Mounting Hardware **OEM Brand Name**

Operating Temperature

Outlet Performance Ivory

Indoor Dry Unless Protected

Mounting Screws Hubbell Wiring Device-

32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)

Straight Blade

• Electrical - Protection Modes - Normal and Common Modes

Electrical - Response Time - Approximately 5 ns

• Electrical - Transient Suppression - Peak Energy (10 X 100 μ s), Peak Current $(8 \times 20 \mu s)$

Electrical - Voltage - 120V AC + 10% - 15%

• Environmental -Flammability - UL 94V-2

Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

Response Time

Series Specification Grade

Туре Duplex

UPC 783585060132

Dimensions

Display Size Standard

Electrical Ratings

15 A Amperage Rating

Terminal Screws Connectivity

Current / Amperage Rating 15 A Current Rating 15 A Frequency Rating 60 Hz Phase Single Phase

Voltage Rating 125 V Voltage Rating Description 125 V

Certifications and Compliance

Industry Standard(s) · CSA Certified to

Specification C22.2 No. 42

• Listed to UL Standards 498

• UL Listed File E2186

Nema Rating 5-15R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Wiring N-13 Catalog page

Catalogs - Wiring Full Catalog

Engineering Drawing - HBL5262ISA AutoCAD Drawing Installation Manuals - WIRING_PD1152_INSTALLINST Literature - SpikeShield® Power Quality Surge Protective

Devices

Literature - Residential Product Guide

Literature - Residential Catalog

Sales Drawings - WDK_HBL5262_DRAWING_PDF Warranty - Industrial & Commercial Products