

Surge Protective Devices, SPIKESHIELD Hospital Grade Surge Suppression Receptacle, **Duplex, 20A 125V, 5-20R, Blue**

By Hubbell Wiring Device-Kellems Catalog # HBL8362SA

Surge Protective Devices, SPIKESHIELD Hospital Grade Surge Suppression Receptacle, Duplex, 20A 125V, 5-20R, Blue



- High-impact nylon face resists breakage
- · Automatic grounding clip attached to bridge
- Power-on indicator light verifies instantly that power is available
- Distinctive surge symbol for visual identification of surge suppression receptacle

Application

Decorator Duplex with Light and Alarm

General

Color **Environmental Conditions** Indoor Dry Unless Protected By Additional Means Indicator(s) Type LED and Audible Alarm Item Type Surge Protection Receptacles Material Composite Material - Mounting Hardware Mounting Screws OFM Brand Name Hubbell Wiring Device-Kellems Operating Temperature 32 Deg F to 140 Deg F (0 Deg C to 60 Deg C) Outlet Straight Blade Performance Electrical - Frequency -

Dimensions

Display Size Standard

Electrical Ratings

20 A Amperage Rating

Connectivity Terminal Screws

Current / Amperage Rating 20 A **Current Rating** 20 A 60 Hz Frequency Rating Phase Single Phase Voltage Rating 125 V

Voltage Rating Description 125 V

Certifications and Compliance

Industry Standard(s) · CSA Certified to

Specification C22.2 No. 42

• Listed to UL Standards 498

Receptacles

• UL Listed File E2186

Nema Rating 5-20R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Wiring M16 Catalog page Catalog Page - Wiring N-13 Catalog page Catalogs - Wiring Full Catalog

Engineering Drawing - HBL8362SA AutoCAD Drawing Installation Manuals - WIRING_PD1152_INSTALLINST Literature - WLBD026 Duct Products Brochure WEB

Literature - Healthcare Application Guide

Literature - SpikeShield® Power Quality Surge Protective

Devices

Sales Drawings - WDK_HBL8362_DRAWING_PDF Warranty - Industrial & Commercial Products

• Electrical - Response Time - Approximately 5 ns • Electrical - Transient Suppression - Peak Energy (10 X 100 μ s) Peak Current $(8 \times 20 \mu s)$ Electrical - Voltage - 120V AC + 10% - 15%Environmental -Flammability - UL 94V-2 Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

Electrical - Protection

Modes - Normal and

Common Modes

Series Hospital Grade
Type Duplex
UPC 783585060552



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved. WDK-HBL8362SA-SPEC-EN | REV 5/2023