HUBBELL
Wiring Device-Kellems

Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 15A 125V, 8 Oulet with CATV, 150 Joules, 6′ Cord, Office White

By Hubbell Wiring Device-Kellems
Catalog # HBL8ESPS1050C

Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 15A 125V, 8 Oulet with CATV, 150 Joules, 6′ Cord, Office White

Features

- Four outlet, 1050 joule SPD features a black housing
- 6 foot cord, 90 degree plug, and two USB ports for charging

Performance

- Electrical - Max Surge Current - 19.5kA
- Electrical - Max. Operating Voltage - 130
- Electrical - Operating Frequency - 50/60Hz
- Environmental - Operating Temperature - -40°F to 160°F (-40°C to 70°C)

General

Catalog Number	HBL8ESPS1050C
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED Indicator
Item Type	Surge Protection Plug Strips
Material	Non-Metallic
Material - Mounting Hardware	Portable
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade 5-15R
Response Time	5
Specifications	• Color - Off. White • Height - 1.44″ (36.6) • Housing - ABS • Length - 10.4″ (264.2) • Width - 3.8″ (96.5)
UPC	783585120638

Dimensions

Display Size	1050 Joules

Electrical Ratings

Amperage Rating	15 A
Connectivity	Plug-In
Current / Amperage Rating	15 A
Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase
Voltage Rating	125 VAC

Logistics

Carton Quantity	20

Product Assets

Catalogs - WDK Catalog Full 2024
Engineering Drawing - HBL8ESPS1050C AutoCAD Drawing
Installation Manuals - WIRING_PD2380_INSTALLINST
Sales Drawings - WDK_HBL8ESPS1050C_DRAWING_PDF
Specifications - HBL8ESPS1050C
Warranty - Surge Plug Strips

©2024 Hubbell Incorporated. All rights reserved