

Replaced by HBL9P105NM, Surge Protective Devices, SPIKESHIELD Surface Mount Block, 100KA 3-Phase 480V AC

By Hubbell Wiring Device-Kellems
Catalog # [HBL9W100C](#)



Surge Protective Devices, SPIKESHIELD Surface Mount Block, 100KA 3-Phase 480V AC

General

Application	Surface Mount Brick with Leads
Catalog Number	HBL9W100C
EU RoHS Indicator	No
Environmental Conditions Indicator(s) Type	Indoor and Outdoor Green Status LED, Audible Alarm
Item Type	Wired-In Branch Panel Protection
Material	Steel
Material - Mounting Hardware	Mounting Screws
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	-40 Degrees F to 149 Degrees F (-40 C to 65 C)
Performance	Electrical - Diagnostics - Green Status LED's, Audible Alarm, Dry Contacts Electrical - Surge Current per Phase - 100kA Environmental - Operating Temperature - -40°F to 140°F (-40°C to 60°C) Mechanical - Terminal Accommodation - #10 AWG 18.0" Wire Leads
Response Time	5
Series	Wired-In Panels
Type	100kA 100kA
UPC	783585120836

Dimensions

Display Size	100kA Peak
--------------	------------

Electrical Ratings

Connectivity	Leads
Frequency Rating	60 Hz
Phase	Three Phase
Voltage Rating	Delta 480 VAC
Voltage Rating Description	480 VAC Delta

Certifications And Compliance

Industry Standard(s)	cULus UL1449-3Rd Edition Type 2 Spd
----------------------	--

Logistics

Carton Quantity	1
-----------------	---

Product Assets

[Catalog Page - WDK M-22 Catalog Page](#)
[Catalog Page - WDK M-6 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - HBL9W100C AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD_HBLxW100C_INSTALLINST Literature - Industrial Solutions](#)
[Literature - SpikeShield® Power Quality Surge Protective Devices](#)
[Sales Drawings - WDK_HBL9W100C_DRAWING_PDF](#)
[Warranty - SPD Series: 320kA, 160kA, 100kA, 120kA, 80MkA & 50kA](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
WDK-HBL9W100C-SPEC-EN | REV 6/2024