HUBBELL
Wiring Device-Kellems

Signal and Control, Mini Quick, Male Plug, Field Attachable, 3-Pole, .39"-.47" Cable Range

By Hubbell Wiring Device-Kellems
Catalog # HPMS03F13

Signal and Control, Mini Quick, Male Plug, Field Attachable, 3-Pole, .39"-.47" Cable Range

Features

- Superior Contact Design
- Body with High Impact Design
- Precision Wire Funnels Eliminate Stray Strands

Application

Quick Connect/Disconnect Signal and Control

Performance

- Electrical - Amperage - 3 Pin - 12A
- 4,5 Pin - 9A
- Electrical - Maximum Wire Size - #16 AWG
- Electrical - Voltage Rating - 250V
- Environmental - Moisture Resistance - IP66 Suitability
- Environmental - Operating Temperature - -40°C to 85°C

General

Catalog Number	HPMS03F13
EU RoHS Indicator	No
Environmental Conditions	IP67 Ingress Protection
Item Type	Male Straight Plug
Material - Coupling Nut	Aluminum
Material - Insert	PUR/PA
Material - O-Ring	Neoprene
Material - Overmold	PBT
Material - Shell	PBT
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	-40 Deg C to 85 Deg C
Specifications	• Connector Insert - PUR/PA • Connector Shell - PBT • Contacts - Brass, gold plate over palladium nickel • Coupling Nut - Anodized aluminum, SST consult factory
Thread Size	Non-Threaded
UPC	783585192079

Electrical Ratings

Amperage Rating	12 A
Current / Amperage Rating	12 A
Current Rating	12 A
Voltage Rating	250V kV

Conductor Related

Cable Size	.39"-.47"
Cable Specification	UL Listed Portable Cord

Certifications And Compliance

Industry Standard(s)	• CSA Certified, C22.2 No. 182.3 and CSA C22.2 No. 94.2-07 • UL 2238 and UL50E, File No. E192071

Logistics

Carton Quantity	30

Product Assets

Catalogs - WDK Catalog Full 2024
Literature - PULP & PAPER SOLUTIONS
Literature - Pulp & Paper Solutions
Sales Drawings - WDK_HPMS03F13_DRAWING_PDF
Specifications - HPMS03F13
Warranty - Industrial & Commercial Products

©2024 Hubbell Incorporated. All rights reserved