

# Surge Protective Devices, SPIKESHIELD IG TVSS Duplex Receptacle with Light and Alarm, 15A 125V, 5-15R, Orange

By Hubbell Wiring Device-Kellems Catalog # IG5262OSA

Surge Protective Devices, SPIKESHIELD IG TVSS Duplex Receptacle with Light and Alarm, 15A 125V, 5-15R, Orange

## Features

- Automatic self-grounding staple
- Distinctive surge symbol provides quick identification
- Power-on indicator light verifies that power is available
- Alert alarm sounds when surge protection is no longer functioning

## Application

Decorator Duplex with Light and Alarm

#### General

Series

| Color                        | <ul><li>Orange</li><li>Orange</li></ul>  |
|------------------------------|--|
| Environmental Conditions     | Indoor Dry Unless Protected<br>By Additional Means   |
| Indicator(s) Type            | LED and Audible Alarm  |
| Item Type                    | Surge Protection Receptacles   |
| Material                     | Composite  |
| Material - Mounting Hardware | Mounting Screws  |
| OEM Brand Name               | Hubbell Wiring Device-<br>Kellems  |
| Operating Temperature        | 32 Deg F to 140 Deg F (0 Deg<br>C to 60 Deg C)   |
| Outlet                       | Straight Blade   |
| Performance                  | <ul> <li>Electrical - Protection<br/>Modes - Normal and<br/>Common Modes</li> </ul>                                      |
|                              | <ul> <li>Electrical - Response Time</li> <li>Approximately 5 ns</li> </ul>   |
|                              | <ul> <li>Electrical - Transient<br/>Suppression - Peak Energy<br/>(10 X 100 μs), Peak Current<br/>(8 X 20 μs)</li> </ul> |
|                              | <ul> <li>Electrical - Voltage - 120V<br/>AC + 10% - 15%</li> </ul>   |
|                              | <ul> <li>Environmental -<br/>Flammability - UL 94V-2</li> </ul>  |
|                              | <ul> <li>Environmental - Operating<br/>Temperature - 32°F to<br/>140°F (0°C to 60°C)</li> </ul>                          |
| Response Time                | 5  |





### **Dimensions**

| Display Size  | Standard  |
|---|---|
| Electrical Ratings  |   |
| Amperage Rating<br>Connectivity<br>Current / Amperage Rating<br>Current Rating<br>Frequency Rating<br>Phase<br>Voltage Rating<br>Voltage Rating Description | 15 A<br>Terminal Screws<br>15 A<br>15 A<br>60 Hz<br>Single Phase<br>125 V<br>125 V  |
| Certifications and Compliance   |   |
| Industry Standard(s)  | <ul> <li>CSA Certified to<br/>Specification C22.2 No. 42</li> <li>Listed to UL Standards 498</li> <li>UL Listed File E2186</li> </ul> |
| Nema Rating   | 5-15R   |

## Logistics

Carton Quantity

## **Product Assets**

Catalog Page - Wiring N-13 Catalog page Catalogs - Wiring Full Catalog Engineering Drawing - IG5262OSA AutoCAD Drawing Installation Manuals - WIRING\_PD1152\_INSTALLINST Literature - SpikeShield® Power Quality Surge Protective Devices Sales Drawings - WDK\_IG5262\_DRAWING\_PDF Warranty - Industrial & Commercial Products

10

## **Related Products**

SS8 - Wallplates and Boxes, Metallic Plates, 1- Gang, 1) Duplex Opening, Standard Size, Stainless Steel

HBL52600WSA - Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5-15R, Office White

IG5362OSA - Surge Protective Devices, SPIKESHIELD IG TVSS Duplex Receptacle with Light and Alarm, 20A 125V, 5-20R, Orange

P8OR - Wallplate, 1-Gang, 1) Duplex, Orange IG8362OSA - Hospital Grade Surge Suppression Receptacle. Style Type UPC Isolated Ground Duplex 783585060637 20A 125V, 5-20R, Office White

HUBBELL

A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved. WDK-IG5262OSA-SPEC-EN | REV 5/2023