HUBBELL
Wiring Device-Kellems

Field Attachable Micro-Quick Control Connectors, Female Straight, 4 Wire, Insulation Displacement

By Hubbell Wiring Device-Kellems
Catalog # MCMS14IDC

Field Attachable Micro-Quick Control Connectors, Female Straight, 4 Wire, Insulation Displacement

Features

- Strain relief bushing protects terminations
- Wire Guide for virtually toolless termination
- Insulation displacement contacts are made of Copper Alloy

Application

Quick Connect/Disconnect Signal and Control

Performance

- Electrical - Amperage - 3A
- Electrical - Cable Diameters - .160″ to .211″
- Electrical - Voltage Rating - 32V AC/DC
- Electrical - Wire Range - #22 AWG max.
- #24 AWG min.
- Environmental - Ingress Protection - IP66 Suitability
- Environmental - Operating Temperature - -20°C to 110°C

General

Catalog Number	MCMS14IDC
Color	Black
EU RoHS Indicator	Yes
Item Type	Female Straight Plug
OEM Brand Name	Hubbell Wiring Device-Kellems
Specifications	• Contact Materials - Copper Alloy • Contact Plating - Tin over Nickel • Housing - Polyester Elastomer, Black • Strain Relief Bushing - Neoprene, Black • Wire Guide - Nylon 6/6, Gray
Temperature Rating	-20 Deg C to 105 Deg C
UPC	783585226699

Dimensions

Diameter Live Part	.59″

Conductor Related

Conductor Type	Copper
Number of Conductors	4-Pole

Certifications And Compliance

Industry Standard(s)	• CSA Certified, C22.2 No. 182.3 and CSA C22.2 No. 94.2-07 • UL 2238 and UL50E, File No. E192071

Logistics

Carton Quantity	25

Product Assets

Catalogs - WDK Catalog Full 2024
Literature - PULP & PAPER SOLUTIONS
Literature - Pulp & Paper Solutions
Sales Drawings - WDK_MCMS14IDC_DRAWING_PDF
Specifications - MCMS14IDC
Warranty - Industrial & Commercial Products

©2024 Hubbell Incorporated. All rights reserved