



Kellems Wire Management, Liquidtight System, Straight, 1/2", Non-Insulated with Mesh

By Hubbell Wiring Device-Kellems
Catalog # [074093402](#)

Kellems® Liquidtight System, Straight, 1/2" Non-Insulated with Mesh.

Features

- Helps prevent conduit pull-out and damage at fitting
- Reduces equipment downtime

Application

1/2" NPT

General

Material	Steel Fitting, Stainless Steel Mesh
Performance	<ul style="list-style-type: none">• Environmental - Flammability - UL 94-HB and UL 94-V2• Environmental - Hazardous Location - Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2• Environmental - Operating Temperature - -30°F to +225°F (-34°C to +107°C)
Series	Liquidtight Conduit
Style	For Metal & Non-Metallic PolyTuff I
Type	<ul style="list-style-type: none">• Straight With Male Fitting• Straight With Male Fitting
UPC	783585331614



Dimensions

Conduit Trade Size 1/2 in

Certifications and Compliance

Industry Standard(s) UL Listed

Logistics

Carton Quantity 10

Product Assets

[Catalog Page - WDK G-42](#) [Catalog Page - WDK W-67](#) [Catalog Page - WDK G-29](#) [Catalog Page - WDK W-58](#) [Catalog Page Catalogs - WDK Catalog Full 2023](#) [Engineering Drawing - 074093402 AutoCAD Drawing](#) [Literature - Wire Management Solutions Brochure](#) [Literature - Wiring Device Solutions for Strategic Manufacturing Facilities](#) [Sales Drawings - WDK_0740934_DRAWINGS_PDF](#) [Warranty - Industrial & Commercial Products](#) [Video - Kellems Wire Management Solutions](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
WDK_CA-074093402-SPEC-EN | REV 1/2024