

Straight Blade Devices,
Receptacles, Duplex, 1/2 Load
Controlled, 15A 125V, 2-Pole 3-Wire
Grounding, Back and Side Wired,
Black

By Hubbell Wiring Device-Kellems
Catalog # [BR15C1BLK](#)



Straight Blade Devices, Receptacles, Duplex, 1/2 Load
Controlled, 15A 125V, 2-Pole 3-Wire Grounding, Back and Side
Wired, Black

Application

Commercial Specification Grade

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-2
- Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG stranded or solid copper wire only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	BR15C1BLK
EU RoHS Indicator	Contact Manufacturer
Horsepower - Maximum	0.5
Item Type	Traditional Duplex
Material	Nylon
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Controlled
Specifications	<ul style="list-style-type: none">• Automatic Self-grounding Staple - Stainless steel• Base - Nylon• Face - Nylon• Ground Contacts - Brass• Mounting Screws - Galvanized Steel• Mounting Strap - .040 in. (1) Galvanized steel• Power Contacts - .030 in. (.8) Brass

Style	Smooth Face
Type	One Controlled Face, Split Circuit
UPC	783585551012

Dimensions

Dimensions	3.28 in x 1.57 in x 1.07 in
Display Size	Standard Sized Product
Height	1.07 in
Length	3.28 in
Weight	0.2 lb
Width	1.57 in

Electrical Ratings

Amperage Rating	15 A
Connectivity	Back and Side Wired
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Voltage Rating	125 V
Voltage Rating Description	125 V

Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none">• CSA Certified 22.2, No. 42• Fed. Spec. W-C-596• NEMA® WD-6 Compliant• UL Listed to UL498 File No. E2186
Nema Rating	5-15R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - WDK A-24 Catalog Page

- Catalogs - WDK Catalog Full 2024
- Literature - Load Control Application Guide
- Literature - Automatic Receptacle Control Product Guide
- Specifications - BR15C1BLK Specification Sheet French
- Specifications - BR15C1BLK Specification Sheet
- Specifications - Wiring BR15C1BLK Specification Sheet
- Warranty - Industrial & Commercial Products



A Hubbell brand