

Straight Blade Devices, Receptacles, Duplex, Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R, Gray, Single Pack

By Hubbell Wiring Device-Kellems Catalog # BR15GRY

Straight Blade Duplex Receptacle, Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-15R.



Features

- · Easy access split circuit tab
- · Nylon face and base
- · Wrap-around galvanized steel strap
- Triple wipe contacts

Application

Commercial Specification Grade

General

Color

Environmental Conditions

Horsepower - Maximum

Item Type

Material

Material - Mounting Hardware

Number Of Poles

Operating Temperature

Performance

Gray

Gris

Indoor Dry Unless Protected

By Additional Means

0.5

Traditional Duplex

Nylon

Screw Mounting

Maximum continuous 75°C and minimum -40°C without

Impact

• Electrical - Current Interrupting - Certified for current interrupting at full rated current

• Electrical - Dielectric

Voltage - Withstands 2,000V minimum

· Environmental -Flammability - UL 94 V-2

Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)

Mechanical - Product Identification - Ratings are a permanent part of the device

Mechanical - Terminal Accommodation - #14-#10 AWG conner stranded or

Dimensions

Dimensions 3.3 in x 1.34 in x 1.1 in Standard Sized Product Display Size

Height 1.1 in Length 3.3 in 0.15 lb Weight Width 1.34 in

Electrical Ratings

Amperage Rating 15 A

Connectivity Back and Side Wired

Current / Amperage Rating 15 A **Current Rating** 15 A

Withstands 2,000V minimum Dielectric Strength

Phase Single Phase

Voltage Rating 125 V Voltage Rating Description 125 V Wattage 1875 W

Conductor Related

Number Of Wires 3-Wire

Wire Size #14 AWG to #10 AWG

Certifications and Compliance

Industry Standard(s)

· Certified to CSA 22.2, No.

42

• Fed. Spec. W-C-596

• NEMA® WD-6 Compliant

UL Listed to UL498 File No.

E2186

Nema Rating 5-15R

Standards - RoHS Compliance CM

Status

Logistics

Carton Quantity 10

Product Assets

Catalog Page - WDK A-29 Catalog Page Catalogs - WDK Catalog Full 2023 Engineering Drawing - M10315 ACAD

solid conductor only

 Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Series

Commercial Specification

Grade

Style

Smooth Face

Туре

Standard DuplexStandard Duplex

UPC

783585127965

Sales Drawings - M10315 Warranty - Industrial & Commercial Products



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. WDK_CA-BR15GRY-SPEC-EN | REV 1/2024