HUBBELL
Wiring Device-Kellems

Straight Blade Devices, Receptacles, Duplex, Tamper-Resistant Duplex, Commercial/Industrial Grade, 2-Pole 3- Wire Grounding, 15A 125V, 5-15R

By Hubbell Wiring Device-Kellems
Catalog # BR15GRYTR

Straight Blade Devices, Receptacles, Duplex, Tamper-Resistant Duplex, Commercial/Industrial Grade, 2-Pole 3- Wire Grounding, 15A 125V, 5-15R, Gray, Single Pack.

Features

- Tamper-resistant shutter complies with national electrical code requirements
- Smooth face
- Wrap-around galvanized steel straps
- Triple wipe contacts

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-2
- Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	BR15GRYTR
EU RoHS Indicator	Yes
Horsepower - Maximum	0.5
Item Type	Traditional Duplex
Material	Nylon
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Commercial Specification Grade
Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - Nylon • Face - Nylon • Ground Contacts - Brass • Mounting Screws - Galvanized Steel • Mounting Strap - .040 in. (1) Galvanized steel • Power Contacts - .030 in. (.8) Brass • Terminal Screws - Plated steel • Wire Clamp - .062 in. (1.6) Nickel plated steel
Style	Smooth Face
UPC	783585144078

Dimensions

Dimensions	3.3 in x 1.58 in x 1.16 in
Display Size	Standard Sized Product
Height	1.16 in
Length	3.3 in
Weight	0.15 lb
Width	1.58 in

Electrical Ratings

Amperage Rating	15 A
Connectivity	Back and Side Wired
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V
Wattage	1875 W

Conductor Related

Number Of Wires	3-Wire

Wire Size	#14 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	• Certified to CSA C22.2, No. 42 • NEMA® WD-6 Compliant • UL Listed to UL498 File No. E2186
Nema Rating	5-15R
Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity	10
Pallet Quantity	8000

Product Assets

Catalog Page - WDK A-30 Catalog Page
Catalogs - WDK Catalog Full 2024
Engineering Drawing - M10511_ACAD
Literature - Tamper-Resistant Receptacles for Education
Literature - Tamper-Resistant Receptacles for Hospitality
Literature - Tamper-Resistant Specification Grade Receptacles
Literature - Tamper-Resistant Receptacles for Daycare
Literature - Tamper-Resistant Receptacles for Assisted Living
Sales Drawings - M10511
Specifications - Wiring BR15GRYTR Specification Sheet
Specifications - BR15GRYTR Specification Sheet French
Warranty - Industrial & Commercial Products
Video - Tamper-Resistant Receptacles

©2024 Hubbell Incorporated. All rights reserved