HUBBELL
Wiring Device-Kellems

Kellems Wire Management, Liquidtight System, 45 Degree Male Liquid Tight Connector, 1″, Steel, Insulated

By Hubbell Wiring Device-Kellems
Catalog # H10041

Kellems Wire Management, Liquidtight System, 45 Degree Male Liquid Tight Connector, 1″, Steel, Insulated.

Features

- Hexagonal nut compresses gland-ring onto conduit
- Nylon gasket provides liquidtight seal at hub
- Non-integral steel ferrule seals conduit

Performance

- Environmental - Operating Temperature - –60°F to +1000°F (–51°C to +538°C)
- Environmental - Hazardous Locations - NEC Reference -Class I, Div. 2 - 501-10(A)(3)B, Class II, Div. 1 - 502-10(A)(2), Class II, Div. 2 - 502-10(A)(3), Class III, Div. 1 - 503-10(A)(2), Class III, Div. 2 - 503-10(B)

General

Catalog Number	H10041
EU RoHS Indicator	Contact Manufacturer
Material	Steel, Zinc Plated
Specifications	• Compression Nut - Zinc plated steel • Ferrule - Zinc plated steel • Fitting - Zinc plated steel • Insulator - Nylon • Locknut - Zinc plated steel • Split Seal Ring - Nylon • Washer - Nylon
Style	45°
UPC	783585035642

Dimensions

Dimension - Thread Size	1″-11-1/2 NPT
Dimension - Width mm	1.719 in
Trade Size	1

Certifications And Compliance

Industry Standard(s)	• CSA Certified • UL 514B

Logistics

Carton Quantity	5

Product Assets

Catalog Page - WDK W-91 Catalog Page
Catalog Page - WDK W-90 Catalog Page
Catalogs - WDK Catalog Full 2024
Engineering Drawing - H10041 AutoCAD Drawing
Installation Manuals - WIRING_PD1857_INSTALLINST
Literature - Wire Management Solutions Brochure
Sales Drawings - WDK_H10041_DRAWINGS_PDF
Specifications - H10041 Specification Sheet French
Specifications - Wiring H10041 Specification Sheet
Warranty - Industrial & Commercial Products
Video - Kellems Wire Management Solutions

©2024 Hubbell Incorporated. All rights reserved